



# Robust Consensus Problem of Heterogeneous Uncertain Second-Order Multi-Agent Systems Based on Sliding Mode Control

Ni ZHAO<sup>1</sup> and Jian-dong ZHU<sup>2\*</sup>

<sup>1</sup>School of Mathematics and Physics Sciences, Anhui Jianzhu University, Hefei, China, <sup>2</sup>Institute of Mathematics, School of Mathematical Sciences, Nanjing Normal University, Nanjing, China

This paper investigates the robust consensus problem for heterogeneous second-order multi-agent systems with uncertain parameters. Based on the sliding mode control method, novel robust consensus protocols are designed for the linear multi-agent systems with uncertain parameters and a class of uncertain nonlinear multi-agent systems. Finally, numerical simulations are given to verify the effectiveness of the proposed protocols.

## OPEN ACCESS

### Edited by:

Ya Zhang,  
Southeast University, China

### Reviewed by:

Liang SUN,  
University of Science and Technology  
Beijing, China  
Dan Ma,  
Northeastern University, China

### \*Correspondence:

Jian-dong ZHU  
zhujiandong@njnu.edu.cn

### Specialty section:

This article was submitted to  
Nonlinear Control,  
a section of the journal  
Frontiers in Control Engineering

**Received:** 19 July 2021

**Accepted:** 08 September 2021

**Published:** 01 October 2021

### Citation:

ZHAO N and  
ZHU J-d (2021) Robust Consensus  
Problem of Heterogeneous Uncertain  
Second-Order Multi-Agent Systems  
Based on Sliding Mode Control.  
Front. Control. Eng. 2:744027.  
doi: 10.3389/fcteg.2021.744027

**Keywords:** sliding mode, control, robust consensus, multi-agent systems, uncertain parameters

## 1 INTRODUCTION

A multi-agent system (MAS) is composed of many subsystems connected by a network, where each subsystem is called an agent. All the agents transmit state information via the interconnecting network and affect each other according to a control protocol. The research topics on multi-agent system theory include mathematical models, simulations, collective behavior analysis, protocol design and so on. Collective behavior analysis of multi-agent systems is an important issue of multi-agent system theory, which has a wide background on physics and engineering such as the self-organization of a colony, coordinated control of robots, synchronization of satellites, formation control of unmanned aerial vehicles (UAVs).

In recent years, many mathematical models of MASs have been widely studied and lots of research contributions have been published Ren and Atkins (2007); Ren and Beard (2005); Ren (2007); Liu and Guo (2008, 2009), including Vicsek model Liu and Guo (2008, 2009); Vicsek et al. (1995), Kuramoto model Kuramoto (1975), integrator multi-agent systems Olfati-Saber et al. (2007); Olfati-Saber and Murray (2004), general high-order linear multi-agent systems Ma and Zhang (2010) and nonlinear multi-agent systems Ren and Chen (2015). A protocol is an interaction rule that specifies the information exchange between an agent and its neighbours on the network. Consensus problem is just to design a protocol such that the states of agents reach consensus, which has been studied from several different perspectives in the existing literatures Olfati-Saber and Murray (2004)-Hou et al. (2009). In Olfati-Saber and Murray (2004); Tang et al. (2012); Xu et al. (2013), consensus protocols for the first order multi-agent systems are developed. While in Islam et al. (2018); Su et al. (2011); Yu et al. (2009), consensus protocols for the second order multi-agent systems are proposed.

For an actual system, it is usually difficult to get an exact mathematical model since uncertain parameters and external disturbances often exist. Thus it is significant to investigate this kind of multi-agent systems with agents having different dynamics and being affected by uncertainties and disturbances. Sliding mode control is an important technique in robust control field, whose main advantage lies in the robustness with respect to uncertainties and disturbances Utkin (1978, 1993);




FIGURE 1 | The digraph of the multi-agent system.

Utkin et al. (2009). At present, sliding mode technique has been used in multi-agent systems to control some collective behaviors. For solving finite-time consensus problem, sliding mode control method has been adopted in many cases Khoo et al. (2009, 2008); Cao et al. (2010); Yu and Long (2015). The well-known high-order sliding mode control is effective in diminishing the chattering phenomenon Levant (1993); Moreno and Osorio (2008) and has been used to solve some formation control problems Jia et al. (2007); Galzi and Shtessel (2006). In Zhang et al. (2017) and Islam et al. (2018), sliding mode control method has been used to solve some consensus problem of multi-agent systems with uncertainties. Some recent results on robust consensus can be seen in Xue et al. (2021) and Yu et al. (2021). In Xue et al. (2021), structured uncertainties are considered, and in Yu et al. (2021) adaptive sliding mode control is designed. In our recent paper Zhao and Zhu (2020), we have investigated a class of linear uncertain multi-agent systems. However, in Zhao and Zhu (2020), one has to solve linear matrix inequalities, and the nonlinear uncertain multi-agent systems have not been considered.

In this paper, we investigate the robust consensus problem for the heterogeneous uncertain second-order multi-agent systems based on sliding mode control. For the linear uncertain multi-agent systems, the uncertain parameters appear in both the state coefficients and the control coefficients. A similar result is obtained for a class of nonlinear multi-agent systems with uncertain parameters. Simulations show the effectiveness of the proposed protocols in realizing robust consensus.

## 2 ROBUST CONSENSUS OF THE LINEAR HETEROGENEOUS SECOND-ORDER MULTI-AGENT SYSTEMS

We consider the networked multi-agent system with the fixed topology  $\mathcal{G} = \{\mathcal{V}, \mathcal{E}, \mathcal{A}\}$ , which is a weighted digraph of order  $m$

with the set of nodes  $\mathcal{V} = \{1, 2, \dots, m\}$ , set of directed edges  $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{V}$ , and a nonnegative adjacency matrix  $\mathcal{A} = (\alpha_{ij})_{m \times m}$ . A directed edge of  $\mathcal{G}$  is denoted by  $j \rightarrow i$ , which means node  $j$  can transmit its state information to node  $i$ . The matrix  $\mathcal{A}$  satisfies

$$\alpha_{ij} \begin{cases} > 0, & j \rightarrow i \in \mathcal{E}, \\ = 0, & \text{otherwise.} \end{cases} \quad (1)$$

Suppose that each node of the digraph is a dynamic agent with dynamics.

$$\dot{x}_i = v_i, \quad (2)$$

$$\dot{v}_i = a_{1i}x_i + a_{2i}v_i + w_i + b_iu_i, \quad (3)$$

where  $(x_i, v_i)^T \in \mathbf{R}^2$  is the state vector,  $u_i(t) \in \mathbf{R}$  the external control,  $a_{1i}$ ,  $a_{2i}$  and  $b_i$  the general uncertain parameters,  $w_i$  the external disturbance. For uncertain multi-agent systems, it is usually to assume that all the agents have the same uncertainty Chen et al. (2010). Obviously, it is more reasonable to admit different uncertainties for different agents. This is just why we call the system as heterogeneous uncertain multi-agent system.

The *robust consensus problem* is just to design a distributed feedback controller  $u_i$  for each  $i = 1, 2, \dots, m$  such that the closed-loop system satisfies

$$\lim_{t \rightarrow \infty} (x_j(t) - x_i(t)) = 0, \quad \lim_{t \rightarrow \infty} (v_j(t) - v_i(t)) = 0, \quad (i, j = 1, \dots, m) \quad (4)$$

for some kinds of uncertain parameters  $a_{1i}$ ,  $a_{2i}$ ,  $b_i$  and external disturbances.

**Assumption 1.** All of the uncertain parameters and the disturbances are uniformly bounded, i.e., there exist known positive constants  $\eta$  and  $\delta$  such that

$$|a_{1i}| \leq \eta, \quad |a_{2i}| \leq \eta, \quad |w_i| \leq \eta, \quad |b_i - b_0| \leq \delta, \quad (5)$$

where  $b_0$  is a known constant and  $\delta < |b_0|$ .




FIGURE 2 | The robust consensus of (Eq. 21) and (Eq. 22).

**Theorem 1.** Consider the heterogeneous uncertain multi-agent system described by Eq. 2 and Eq. 3. If digraph  $\mathcal{G}$  has a spanning tree and Assumption 1 holds, then the robust consensus problem is solved by the distributed sliding mode controller

$$u_i = -\frac{1}{b_0} (L_i + \eta) \text{sgn}(s_i), \tag{6}$$

where

$$L_i = \frac{\eta |x_i| + \eta |v_i| + \eta}{1-r} + \frac{k}{1-r} \sum_{j=1}^m \alpha_{ij} |v_j - v_i|, \tag{7}$$

$$s_i = v_i - k \sum_{j=1}^m \alpha_{ij} (x_j - x_i), \tag{8}$$

$$0 < r = \frac{\delta}{b_0} < 1 \text{ and } k > 0$$

**Proof.** First, we prove that the trajectory of the closed-loop system will stay in the sliding surfaces  $s_i = 0$  ( $i = 1, 2, \dots, m$ ) after a finite time. Let  $V_i = \frac{s_i^2}{2}$ . Then

$$\begin{aligned} \dot{V}_i &= s_i \dot{s}_i \\ &= s_i (a_{1i}x_i + a_{2i}v_i + w_i + b_i u_i - k \sum_{j=1}^m \alpha_{ij} (v_j - v_i)) \\ &= s_i (a_{1i}x_i + a_{2i}v_i + w_i - k \sum_{j=1}^m \alpha_{ij} (v_j - v_i) + b_0 \left(1 + \frac{b_i - b_0}{b_0}\right) u_i) \\ &= s_i (a_{1i}x_i + a_{2i}v_i + w_i - k \sum_{j=1}^m \alpha_{ij} (v_j - v_i) + \left(1 + \frac{b_i - b_0}{b_0}\right) u_i^*). \end{aligned} \tag{9}$$

By Eq. 7, it is easy to see

$$\begin{aligned} &\left| \frac{a_{1i}x_i + a_{2i}v_i + w_i - k \sum_{j=1}^m \alpha_{ij} (v_j - v_i)}{1 + \frac{b_i - b_0}{b_0}} \right| \\ &\leq \frac{\eta |x_i| + \eta |v_i| + \eta}{1-r} + \frac{|k|}{1-r} \sum_{j=1}^m \alpha_{ij} |v_j - v_i| \\ &= L_i. \end{aligned} \tag{10}$$

By Eq. 9, we have




FIGURE 3 | The robust consensus of (Eq. 21) and (Eq. 22).

$$\begin{aligned}
 \dot{V}_i &\leq \left(1 + \frac{b_i - b_0}{b_0}\right) |s_i| L_i + \left(1 + \frac{b_i - b_0}{b_0}\right) s_i u_i^* \\
 &= \left(1 + \frac{b_i - b_0}{b_0}\right) |s_i| L_i - \left(1 + \frac{b_i - b_0}{b_0}\right) s_i (L_i + \eta) \text{sgn}(s_i) \\
 &= -\left(1 + \frac{b_i - b_0}{b_0}\right) \eta |s_i| \\
 &\leq -(1 - r)\eta |s_i| \\
 &= -\sqrt{2}(1 - r)\eta V_i^{1/2} < 0.
 \end{aligned}
 \tag{11}$$

From Eq. 11, one obtains that  $s_i(t) = 0$  as  $t \geq \max_{1 \leq i \leq m} \frac{\sqrt{2V_i(0)}}{(1-r)\eta}$ .

Second, we consider the dynamics limited on the sliding mode surfaces. While the trajectory stays in the sliding mode surfaces  $s_i = 0$ , we have


$$v_i - k \sum_{j=1}^m \alpha_{ij} (x_j - x_i) = 0.
 \tag{12}$$

From Eq. 12 and Eq. 2, it follows that the dynamics limited on the sliding mode surfaces is described by

$$\dot{x}_i = -k \sum_{j=1}^m \alpha_{ij} (x_j - x_i), \quad i = 1, 2, \dots, m.
 \tag{13}$$

In Olfati-Saber and Murray (2004), the consensus of system (13) has been proved as follows: there exists a constant  $C$ , which is dependent on the initial states  $(x_1(0), x_2(0), \dots, x_m(0))^T$ , such that  $x_i(t) \rightarrow C$  as  $t \rightarrow +\infty$  for every  $1 \leq i \leq m$ . Considering each sliding mode function  $s_i$  described by Eq. 8, we conclude by  $s_i = 0$  that  $v_i(t) \rightarrow 0$  as  $t \rightarrow +\infty$ . Therefore, the consensus described by Eq. 4 is realized.

**Remark 1.** The proposed conditions are somewhat conservative since the designed controller depends on the bounds of the uncertain parameters. If the bounds are unknown, one can consider adopt adaptive control method. In many practical systems, there are errors in the measurement of parameters, but generally speaking the measurement accuracy of the instrument is known. Therefore, in this case the variation range of parameters in Assumption 1 can be accurately determined. Moreover, the boundary of disturbance signals needs to be obtained through experience and experiments.



### 3 ROBUST CONSENSUS OF A CLASS OF UNCERTAIN NONLINEAR MULTI-AGENT SYSTEMS

In this section, we consider a kind of uncertain nonlinear multi-agent systems. Suppose that each node of the digraph has a nonlinear dynamics as follows:

$$\dot{x}_i = v_i, \tag{14}$$

$$\dot{v}_i = a_i(x_i, v_i) + b_i(x_i, v_i)u_i, \tag{15}$$

where  $(x_i(t), v_i(t))^T \in \mathbf{R}^2$  is the state vector of the  $i$ th agent,  $u_i(t) \in \mathbf{R}$  is the control,  $a_i(x_i, v_i)$  and  $b_i(x_i, v_i)$  are uncertain nonlinear functions for every  $i = 1, 2, \dots, m$ .

**Assumption 2.** For the uncertain nonlinear functions  $a_i(x_i, v_i)$  and  $b_i(x_i, v_i)$ , there exists a known function  $L(x_i, v_i)$  satisfying

$$\left| \frac{a_i(x_i, v_i)}{b_i(x_i, v_i)} \right| \leq L(x_i, v_i), \tag{16}$$

where  $b_i(x_i, v_i) \geq b_0$  for known constant  $b_0 > 0$ .

**Theorem 2.** For the uncertain nonlinear multi-agent system described by Eq. 14 and Eq. 15, If digraph  $\mathcal{G}$  has a spanning tree

and Assumption 2 holds, then the robust consensus problem of the system can be solved by the distributed sliding mode controller

$$u_i = -\beta_i \text{sgn}(s_i), \tag{17}$$

where

$$\beta_i = L(x_i, v_i) + \frac{k}{b_0} \sum_{j=1}^m \alpha_{ij} |v_j - v_i| + \beta_0 \tag{18}$$

with a known constant  $\beta_0 > 0$  and

$$s_i = v_i - k \sum_{j=1}^m \alpha_{ij} (x_j - x_i) \tag{19}$$

with any constant  $k > 0$ .

**Proof.** Let  $V_i = \frac{s_i^2}{2}$ . Then

$$\begin{aligned} \dot{V}_i &= s_i \dot{s}_i \\ &= s_i \left( \dot{v}_i - k \sum_{j=1}^m \alpha_{ij} (\dot{x}_j - \dot{x}_i) \right) \\ &= s_i \left( a_i(x_i, v_i) + b_i(x_i, v_i)u_i - k \sum_{j=1}^m \alpha_{ij} (v_j - v_i) \right) \end{aligned}$$




FIGURE 5 | The robust consensus of (Eq. 24) and (Eq. 25).

$$\begin{aligned}
 &= s_i \left( a_i(x_i, v_i) - k \sum_{j=1}^m \alpha_{ij} (v_j - v_i) \right) + s_i b_i(x_i, v_i) u_i \\
 &= s_i b_i(x_i, v_i) \frac{a_i(x_i, v_i) - k \sum_{j=1}^m \alpha_{ij} (v_j - v_i)}{b_i(x_i, v_i)} + s_i b_i(x_i, v_i) u_i.
 \end{aligned}$$

Applying Assumption 2, (17) and (18), we have

$$\begin{aligned}
 \dot{V}_i &\leq |s_i| b_i(x_i, v_i) \left( L(x_i, v_i) + \frac{k}{g_0} \sum_{j=1}^m \alpha_{ij} |v_j - v_i| \right) + s_i b_i(x_i, v_i) u_i \\
 &= b_i(x_i, v_i) |s_i| \left( L(x_i, v_i) + \frac{k}{g_0} \sum_{j=1}^m \alpha_{ij} |v_j - v_i| \right) - b_i(x_i, v_i) s_i \text{sgn}(s_i) \beta \\
 &= b_i(x_i, v_i) |s_i| \left( L(x_i, v_i) + \frac{k}{g_0} \sum_{j=1}^m \alpha_{ij} |v_j - v_i| - \beta \right) \\
 &= -b_i(x_i, v_i) \beta_0 |s_i| \\
 &\leq -b_0 \beta_0 |s_i| \\
 &= -\sqrt{2} b_0 \beta_0 V_i^{1/2}.
 \end{aligned} \tag{20}$$

From Eq. 20, it follows that  $s_i(t) = 0$  as  $t \geq \max_{1 \leq i \leq m} \frac{\sqrt{2V_i(0)}}{b_0 \beta_0}$ .

The rest of the proof is as same as that of the proof of Theorem 1.

**Remark 2.** In practice, the upper bound functions satisfying Assumption 2 are also needed to be designed via experience and experiments. The bound of nonlinearity is used to design the controller, which can lead to high-gain feedback. This is a disadvantage of our paper.

### 4 SIMULATIONS

**Example 1.** Consider the multi-agent systems with the topology  $\mathcal{G}$  shown in Figure 1 and the dynamics as follows

$$\dot{x}_i = v_i, \tag{21}$$

$$\dot{v}_i = a_{1i} x_i + a_{2i} v_i + w_i + b_i u_i, \tag{22}$$

where  $i = 1, 2, \dots, 10$ . Let  $x = [x_1, x_2, \dots, x_{10}]$  and  $v = [v_1, v_2, \dots, v_{10}]$  be the position vector and the velocity vector of the multi-agent system. Let  $a_1 = [a_{11}, a_{12}, \dots, a_{1,10}]$ ,  $a_2 = [a_{21}, a_{22}, \dots, a_{2,10}]$  and  $b = [b_1, b_2, \dots, b_{10}]$  be the uncertain parameters satisfying  $|a_{ij}| \leq 0.3$ ,  $|b_i - 1| \leq 0.3$ . Let  $w(t) = [w_1(t), w_2(t), \dots, w_{10}(t)]$  be composed of the disturbance signals satisfying  $|w_i(t)| \leq 0.3$ . By Figure 1, the adjacency matrix of  $\mathcal{G}$  is




FIGURE 6 | The robust consensus of (Eq. 24) and (Eq. 25).

$$A = \begin{bmatrix} 0 & 2 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 3 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 5 & 0 & 0 & 0 & 4 & 0 & 0 \\ 0 & 0 & 0 & 0 & 2 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 2 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 2 & 0 & 0 & 2 & 0 & 0 & 0 & 3 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 2 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \\ 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \quad (23)$$

$$\begin{aligned} x(0) &= [-2, 3, -2, 3, 1, -6, 4, 5, 6, -7], \quad v(0) = [4, -2, 6, 4, 9, 6, -9, 6, -4, 3], \\ a_1 &= [-0.1, 0.3, 0.3, -0.05, 0.2, 0.1, 0.15, -0.2, 0.3, -0.2], \\ a_2 &= [0.3, 0.1, 0.15, -0.2, -0.3, 0.3, -0.2, 0.1, -0.1, 0.1], \\ b &= [1.2, 1.3, 0.9, 0.7, 1.1, 1.1, 0.7, 1.2, 0.7, 1.2], \\ w(t) &= [-0.2 \sin(t), 0.1 \cos(t), 0.15 \sin(2t), 0.2, 0.1, -0.25, -0.2, 0.2, 0.1, -0.2 \sin(t)]. \end{aligned}$$

and

$$\begin{aligned} x(0) &= [2, -3, 2, 3, 1, -1, 4, 3, -4, -2], \quad v(0) = [4, 2, -3, 4, 3, 4, -3, -3, -2, 4], \\ a_1 &= [-0.2, 0.1, 0.25, -0.15, 0.1, 0.3, -0.15, -0.3, -0.3, 0.12], \\ a_2 &= [0.2, 0.15, -0.15, -0.25, 0.13, 0.23, 0.2, 0.3, -0.2, 0.15], \\ b &= [1.3, 1.1, 0.8, 1.3, 0.8, 1.2, 0.8, 1.3, 0.7, 0.9], \\ w(t) &= [0.3 \sin(t), -0.1, -0.2, 0.3 \cos(t), 0.2, -0.2, -0.3, -0.2, 0.3 \sin(2t), 0.3], \end{aligned}$$

The controller is designed as (6)–(8) with  $\eta = \delta = 0.3, k = 1, b_0 = 1$  and  $r = \delta/b_0 = 0.3$ . In order to show the robustness of the designed controller, we choose three groups of parameters and disturbance signals in the simulations. In Figure 2, the time response curves and the first control component are displayed with

$$\begin{aligned} x(0) &= [2, 3, 2, 3, 2, 6, 4, 3, 2, 4], \quad v(0) = [3, 2, 5, 4, 1, 6, 9, 6, 4, 3], \\ a_1 &= [0.1, 0.2, -0.3, 0.05, 0.2, -0.1, 0.05, -0.3, 0.1, 0], \\ a_2 &= [0.2, -0.1, 0.05, 0.2, -0.3, 0.05, -0.2, 0.1, 0.1, -0.1], \\ b &= [1.1, 1.2, 0.9, 0.8, 1.1, 1.2, 1.2, 0.9, 0.8, 1.1], \\ w &= [0.2, -0.1, 0.05, 0.2, -0.1, 0.05, -0.2, 0.1, 0.1, -0.1]. \end{aligned}$$

In the simulations shown in Figure 3 and Figure 4, we set

respectively. From Figure 2, Figure 3 and Figure 4, we see that the controller is robust for the parameters and disturbances. From the time response curves of  $u_1(t)$ , we see that the typical characteristic chattering phenomenon exists in the sliding mode control.

**Example 2.** Consider a practical multi-agent system: a dynamical network composed of pendulums:

$$\dot{\theta}_i = \omega_i, \quad (24)$$

$$\dot{\omega}_i = -\frac{g_0}{l_i} \sin(\theta_i) - \frac{k_0}{m_i} \omega_i + \frac{1}{ml_i^2} T_i, \quad (25)$$



where  $\theta_i$ ,  $\omega_i$ ,  $T_i$ ,  $m_i$ , and  $l_i$  are angular displacement, angular velocity, external torque, mass, and length of the  $i$ th pendulum, respectively. The constants  $k_0$  and  $g_0$  are coefficient of friction and acceleration due to the gravity, respectively. The known parameter information include  $0.05 < m_i < 0.2$ ,  $0.9 < l_i < 1.1$ ,  $0.01 < k_0 < 0.05$ , and  $9.8 < g_0 < 9.9$ . By Theorem 2, we need to determine  $L(\theta_i, \omega_i)$  satisfying Assumption 2. It is easy to check that

$$\left| \frac{-\frac{g_0}{l_i} \sin(\theta_i) - \frac{k_0}{m_i} \omega_i}{\frac{1}{m_i l_i^2}} \right| \leq m_i l_i g_0 |\sin(\theta_i)| + k_0 l_i^2 |\omega_i| \leq 2.178 |\sin(\theta_i)| + 0.0605 |\omega_i|. \quad (26)$$

By Eq. 26, we let  $L_i(\theta_i, \omega_i) = 2.178 |\sin(\theta_i)| + 0.0605 |\omega_i|$ . Since  $\frac{1}{m_i l_i^2} \geq 4.1322$ , one can let  $b_0 = 4$ . So the controller can be determined by Eq. 17–Eq. 19. The simulations are performed by using  $k = \beta_0 = 1$  and the digraph shown in Figure 1. Figure 5 and Figure 6 show the robust consensus of the closed-loop system with two group of parameter.

## 5 CONCLUSION

In this paper, we have investigated the robust consensus problem for the heterogeneous uncertain second order multi-agent systems based on sliding mode control. Novel robust consensus protocols have been proposed based on sliding mode control to realize the consensus. Numerical simulations have shown the effectiveness of the proposed protocols. The main disadvantage lies in the chattering

## REFERENCES

- Cao, Y., Ren, W., and Meng, Z. (2010). Decentralized Finite-Time Sliding Mode Estimators and Their Applications in Decentralized Finite-Time Formation Tracking. *Syst. Control. Lett.* 59, 522–529. doi:10.1016/j.sysconle.2010.06.002
- Chen, T., Zhu, J., and Shi, Y. (2010). Leader-follower Coordination of Linear Time-Invariant Multi-Agent Systems. *Dyn. Continuous, Discrete Impulsive Syst. Ser. B: Appl. Algorithms* 17, 431–448.
- Galzi, D., and Shtessel, Y. (2006). “Uav Formations Control Using High Order Sliding Modes,” in 2006 American Control Conference, June 14–16, 2006, Minneapolis, MN (IEEE), 4249–4254. doi:10.1109/acc.2006.1657386
- Hou, Z.-G., Cheng, L., and Tan, M. (2009). Decentralized Robust Adaptive Control for the Multiagent System Consensus Problem Using Neural Networks. *IEEE Trans. Syst. Man, Cybern. B* 39, 636–647. doi:10.1109/tsmcb.2008.2007810
- Islam, S., Khawli, T. A., Alzaabi, A., and Sunda-Meya, A. (2018). “Consensus Based Distributed Robust Adaptive Control for Second-Order Nonlinear Multi-Agent Systems with Uncertainty,” in The 2018 IEEE International Conference on Systems, Man, and Cybernetics, October 7–10, 2018, Miyazaki, Japan (IEEE), 2639–2644. doi:10.1109/smc.2018.00451
- Jia, Q., Xing, X., and Li, G. (2007). “Formation Path Tracking Controller of Multiple Robot System by High Order Sliding Mode,” in 2007 IEEE International Conference on Automation and Logistics, August 18–21, 2007, Jinan, China (IEEE), 923–927. doi:10.1109/ical.2007.4338698
- Khoo, S., Xie, L., and Man, Z. (2009). Robust Finite-Time Consensus Tracking Algorithm for Multirobot Systems. *Ieee/asme Trans. Mechatron.* 14, 219–228. doi:10.1109/tmech.2009.2014057

phenomenon of the designed controller. How to reduce the chattering phenomenon will be discussed in our future research work.

## DATA AVAILABILITY STATEMENT

The original contributions presented in the study are included in the article/Supplementary Material, further inquiries can be directed to the corresponding author.

## AUTHOR CONTRIBUTIONS

All authors listed have made a substantial, direct, and intellectual contribution to the work and approved it for publication.

## FUNDING

This work is supported by Young Scholar Project of Anhui Jianzhu University under grant 2016XQZ08 and National Natural Science Foundation (NNSF) of China under Grants 61628302.

## SUPPLEMENTARY MATERIAL

The Supplementary Material for this article can be found online at: <https://www.frontiersin.org/articles/10.3389/fcteg.2021.744027/full#supplementary-material>

- Khoo, S., Xie, L., Yu, Z., and Man, Z. (2008). “Finite-time Consensus Algorithm of Multi-Agent Networks,” in 2008 10th International Conference on Control, Automation, Robotics and Vision, October 17–20, 2008, Hanoi, Vietnam (IEEE), 916–920. doi:10.1109/icarcv.2008.4795640
- Kuramoto, Y. (1975). “Self-entrainment of a Population of Coupled Non-linear Oscillators,” in International symposium on mathematical problems in the theoretical physics (Berlin, Heidelberg: Springer), 420–422.
- Levant, A. (1993). Sliding Order and Sliding Accuracy in Sliding Mode Control. *Int. J. Control.* 58, 1247–1263. doi:10.1080/00207179308923053
- Liu, Z., and Guo, L. (2008). Connectivity and Synchronization of Vicsek Model. *Sci. China Ser. F-inf. Sci.* 51, 848–858. doi:10.1007/s11432-008-0077-2
- Liu, Z., and Guo, L. (2009). Synchronization of Multi-Agent Systems without Connectivity Assumptions. *Automatica* 45, 2744–2753. doi:10.1016/j.automatica.2009.09.015
- Ma, C.-Q., and Zhang, J.-F. (2010). Necessary and Sufficient Conditions for Consensusability of Linear Multi-Agent Systems. *IEEE Trans. Automat. Contr.* 55, 1263–1268. doi:10.1109/tac.2010.2042764
- Moreno, J. A., and Osorio, M. (2008). “A Lyapunov Approach to Second-Order Sliding Mode Controllers and Observers,” in 2008 47th IEEE Conference on Decision and Control, December 9–11, 2008, Cancun, Mexico (IEEE), 2856–2861. doi:10.1109/cdc.2008.4739356
- Olfati-Saber, R., Fax, J. A., and Murray, R. M. (2007). Consensus and Cooperation in Networked Multi-Agent Systems. *Proc. IEEE* 95, 215–233. doi:10.1109/jproc.2006.887293
- Olfati-Saber, R., and Murray, R. M. (2004). Consensus Problems in Networks of Agents with Switching Topology and Time-Delays. *IEEE Trans. Automat. Contr.* 49, 1520–1533. doi:10.1109/tac.2004.834113



- Ren, W., and Beard, R. W. (2005). Consensus Seeking in Multiagent Systems under Dynamically Changing Interaction Topologies. *IEEE Trans. Automat. Contr.* 50, 655–661. doi:10.1109/tac.2005.846556
- Ren, C. E., and Chen, C. L. P. (2015). Sliding Mode Leader-following Consensus Controllers for Second-order Non-linear Multi-agent Systems. *IET Control. Theor. Appl.* 9, 1544–1552. doi:10.1049/iet-cta.2014.0523
- Ren, W., and Atkins, E. (2007). Distributed Multi-Vehicle Coordinated Control via Local Information Exchange. *Int. J. Robust Nonlinear Control.* 17, 1002–1033. doi:10.1002/rnc.1147
- Ren, W. (2007). Distributed Attitude Alignment in Spacecraft Formation Flying. *Int. J. Adapt. Control. Signal. Process.* 21, 95–113. doi:10.1002/acs.916
- Su, H., Chen, G., Wang, X., and Lin, Z. (2011). Adaptive Second-Order Consensus of Networked mobile Agents with Nonlinear Dynamics. *Automatica* 47, 368–375. doi:10.1016/j.automatica.2010.10.050
- Tang, Y., Gao, H., Zou, W., and Kurths, J. (2012). Distributed Synchronization in Networks of Agent Systems with Nonlinearities and Random Switchings. *IEEE Trans. Cybern* 43, 358–370. doi:10.1109/TSMCB.2012.2207718
- Utkin, V., Guldner, J., and Shi, J. (2009). *Sliding Mode Control in Electro-Mechanical Systems*. Boca Raton, FL: CRC Press.
- Utkin, V. I. (1993). Sliding Mode Control Design Principles and Applications to Electric Drives. *IEEE Trans. Ind. Electron.* 40, 23–36. doi:10.1109/41.184818
- Utkin, V. (1978). Methods for Constructing Discontinuity Planes in Multidimensional Variable Structure Systems. *Automation and remote Control* 39, 1466–1470.
- Vicsek, T., Czirók, A., Ben-Jacob, E., Cohen, I., and Shochet, O. (1995). Novel Type of Phase Transition in a System of Self-Driven Particles. *Phys. Rev. Lett.* 75, 1226–1229. doi:10.1103/physrevlett.75.1226
- Xu, J., Xie, L., Li, T., and Lum, K. Y. (2013). Consensus of Multi-agent Systems with General Linear Dynamics via Dynamic Output Feedback Control. *IET Control. Theor. Appl.* 7, 108–115. doi:10.1049/iet-cta.2012.0221
- Xue, X., Wu, F., and Yuan, C. (2021). Robust Consensus for Linear Multi-Agent Systems with Structured Uncertainties. *Int. J. Control.* 94, 675–686. doi:10.1080/00207179.2019.1612096
- Yu, S., and Long, X. (2015). Finite-time Consensus for Second-Order Multi-Agent Systems with Disturbances by Integral Sliding Mode. *Automatica* 54, 158–165. doi:10.1016/j.automatica.2015.02.001
- Yu, W., Chen, G., Cao, M., and Kurths, J. (2009). Second-order Consensus for Multiagent Systems with Directed Topologies and Nonlinear Dynamics. *IEEE Trans. Syst. Man. Cybern B Cybern* 40, 881–891. doi:10.1109/TSMCB.2009.2031624
- Yu, Z., Yu, S., Jiang, H., and Hu, C. (2021). Distributed Consensus for Multi-Agent Systems via Adaptive Sliding Mode Control. *Int. J. Robust Nonlinear Control.* 31, 7125–7151. doi:10.1002/rnc.5670
- Zhang, J., Lyu, M., Shen, T., Liu, L., and Bo, Y. (2017). Sliding Mode Control for a Class of Nonlinear Multi-Agent System with Time Delay and Uncertainties. *IEEE Trans. Ind. Electro.* 65, 865–875. doi:10.1109/TIE.2017.2701777
- Zhao, N., and Zhu, J. (2020). Sliding Mode Control for Robust Consensus of General Linear Uncertain Multi-Agent Systems. *Int. J. Control. Autom. Syst.* 18, 2170–2175. doi:10.1007/s12555-019-0817-7

**Conflict of Interest:** The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

**Publisher's Note:** All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors and the reviewers. Any product that may be evaluated in this article, or claim that may be made by its manufacturer, is not guaranteed or endorsed by the publisher.

Copyright © 2021 ZHAO and ZHU. This is an open-access article distributed under the terms of the Creative Commons Attribution License (CC BY). The use, distribution or reproduction in other forums is permitted, provided the original author(s) and the copyright owner(s) are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.