



An Overview on the Conversion of Forest Biomass into Bioenergy

Qing Yu^{1,2}, Yacheng Wang¹, Quyet Van Le³, Han Yang¹, Homa Hosseinzadeh-Bandbafha⁴, Yafeng Yang¹, Christian Sonne^{1,5}, Meisam Tabatabaei^{1,4,6,7}, Su Shiung Lam^{1,6} and Wanxi Peng^{1*}

¹Henan Province International Collaboration Lab of Forest Resources Utilization, School of Forestry, Henan Agricultural University, Zhengzhou, China, ²School of Psychology, Northeast Normal University, Changchun, China, ³Institute of Research and Development, Duy Tan University, Da Nang, Vietnam, ⁴Biofuel Research Team (BRTeam), Terengganu, Malaysia, ⁵Arctic Research Centre (ARC), Department of Bioscience, Aarhus University, Roskilde, Denmark, ⁶Higher Institution Centre of Excellence (HiCoE), Institute of Tropical Aquaculture and Fisheries (AKUATROP), Universiti Malaysia Terengganu, Terengganu, Malaysia, ⁷Microbial Biotechnology Department, Agricultural Biotechnology Research Institute of Iran (ABRII), Agricultural Research, Education, and Extension Organization (AREEO), Karaj, Iran

OPEN ACCESS

Edited by:

Ao Xia,
Chongqing University, China

Reviewed by:

Cheng Tung Chong,
Shanghai Jiao Tong University, China
Richa Arora,
Punjab Agricultural University, India

*Correspondence:

Wanxi Peng
pengwanxi@163.com

Specialty section:

This article was submitted to
Bioenergy and Biofuels,
a section of the journal
Frontiers in Energy Research

Received: 24 March 2021

Accepted: 21 June 2021

Published: 02 July 2021

Corrected: 03 December 2025

Citation:

Yu Q, Wang Y, Van Le Q, Yang H, Hosseinzadeh-Bandbafha H, Yang Y, Sonne C, Tabatabaei M, Lam SS and Peng W (2021) An Overview on the Conversion of Forest Biomass into Bioenergy. *Front. Energy Res.* 9:684234. doi: 10.3389/fenrg.2021.684234

Biomass plays a crucial role in mitigating the concerns associated with increasing fossil fuel combustion. Among various types of biomass, forest biomass has attracted considerable attention given its abundance and variations. In this work, an overview is presented on different pathways available to convert forest biomass into bioenergy. Direct use of forest biomass could reduce carbon dioxide emissions associated with conventional energy production systems. However, there are certain drawbacks to the direct use of forest biomass, such as low energy conversion rate and soot emissions and residues. Also, lack of continuous access to biomass is a severe concern in the long-term sustainability of direct electricity generation by forest biomass. To solve this problem, co-combustion with coal, as well as pelletizing of biomass, are recommended. The co-combustion of forest biomass and coal could reduce carbon monoxide, nitrogen oxides, and sulfide emissions of the process. Forest biomass can also be converted into various liquid and gaseous biofuels through biochemical and thermochemical processes, which are reviewed and discussed herein. Despite the favorable features of forest biomass conversion processes to bioenergy, their long-term sustainability should be more extensively scrutinized by future studies using advanced sustainability assessment tools such as life cycle assessment, exergy, etc.

Keywords: forestry, biomass, biodiesel, biogas, energy

INTRODUCTION

Greenhouse gases (GHGs) emissions and other harmful gases are among the primary global concern, mainly caused by the increasing use of fossil energy carriers (Jun-jun and Da-rui, 2012). GHGs have been thought of as a critical factor in global warming that plays a crucial role in climate change (Panahi et al., 2020b). Extensive research has shown that using other carbon sources like biomass could reduce these concerns (Hosseinzadeh-Bandbafha et al., 2018). In the literature available on the application of biomass to generate energy, the relative importance of forest biomass is debated (Vassilev et al., 2010; Gustavsson et al., 2015). Generally, the forest biomass is classified into fuelwood and industrial roundwood (Raunikar et al., 2010). Fuelwood is harvested from forestlands and directly combusted for useable heat or converted into bioenergy and biofuel and used to generate



FIGURE 1 | Distribution of research activities on forest biomass to replace fossil-based energy carriers globally and the research interrelations between different countries.

TABLE 1 | Statistics by the EU on energy generation from different types of forest biomass in 2010 and estimated values in 2030.

Biomass species	Biomass potential (TJ × 10 ⁴)		References
	2010	2030	
Forest residues	180	163–301	Moiseyev et al. (2014)
Wood processing	419	427	Searle and Malins (2016)
Forest crops	180–193	427–615	Böttcher and Graichen (2015)
Total	779–792	1,017–1,343	

heat and power. More specifically, due to the high content of macromolecular sugars such as cellulose and organic matter, fuelwood is a promising feedstock for thermochemical conversion, biological conversion, liquefaction, and gasification (Perez-Garcia et al., 2005; Tan et al., 2015). Forest biomass can be used in co-combustion with fossil fuels or alone in boilers and other equipment of power generation (Scarlat et al., 2011; Calvo et al., 2013). Accordingly, when countries set their macro strategies related to energy development, efficient utilization of forest biomass resources to solve environmental crises is strongly considered (Figure 1). For example, among the available energy sources in China, 54.2% of forest biomass is used to generate power and fuel (Liao et al., 2004).

It is reported that the energy generated by forest biomass can support 15.4% of the total human energy consumption (Welfle et al., 2014). During the period 2004–2015, the whole power generation from forest biomass stood at around one million kW/yr, contributing to the elimination of forest residues and achieving ecological-zero carbon dioxide (CO₂) emissions (Ince et al., 2011; Nunes et al., 2018). For instance, forest biomass application as a replacement for fossil energy in Australia reduces atmospheric CO₂ emissions by 25 million tons annually (Zomer et al., 2008; Pour et al., 2018). Furthermore, the European Union (EU) statistics show that there is an increasing trend for total energy that forest waste

can provide for human consumption from 2010 to 2030 (Table 1) (Urban et al., 2010).

In light of the significance of forest biomass in the global energy market in the future, the present work aims to briefly report on various methods of forest biomass conversion into bioenergy and biofuels.

DIRECT UTILIZATION OF FOREST BIOMASS

Direct Combustion of Wood for Energy Production

A significant advantage of forest biomass is that it could be directly combusted. Direct combustion is a thermochemical process during which biomass burns in the open air, and the photosynthetically stored chemical energy of the biomass is converted into heat (Lam et al., 2019). Although direct combustion of forest biomass leads to the emissions of CO₂, particulates (PM_{2.5}), sulfur dioxide (SO₂), and other harmful substances, their amounts are still less than those caused by the combustion of fossil fuels (Karaj et al., 2010; Kacprzak et al., 2016). For example, previous research has established that the direct combustion of forest biomass generates 20% less CO₂ emissions than fossil fuels (Froese et al., 2010). However, there

TABLE 2 | CO₂ emission reduction potentials of biomass-based power plants compared to their fossil fuel-based counterparts.

Types of biomass	Country/Region	Types of power plants	Capacity of power plant	CO ₂ emission reduction (t/yr)	References
Forest waste (wood chips, wood pellets, and black pellets)	Japan, Tohoku region	Thermal power plant	500 MW	198,000–252,000	(Furubayashi and Nakata, 2018)
Forest waste	Portugal, Harbor of Sines	Thermal power plant	314 MW	1,000,000	(Nunes et al., 2014)
Palm tree waste	Iran, Bushehr Province	Rankine cycle steam power plant	8 MW	40,500	(Mallaki and Fatehi, 2014)
Forest waste (woody biomass)	Japan	Thermal power plant	5.7 MW	30,934	(Nakano et al., 2015)
Forest waste (wood chips)	United States	Thermal power plant	70 MW	552,032	(Campbell and Mika, 2009)

are certain drawbacks associated with the use of forest biomass. One of these is the low energy conversion rate; moreover, direct combustion leads to soot and residues (Hong-ru and Yi-hu, 2007).

Direct combustion of biomass for power generation has continued since the 1990s (Yin et al., 2008). Biomass-fired combined heat and power (CHP) plants include a vibrating grate boiler, condensing steam turbine, and electric generator (Chen et al., 2021). The vibrating grate boiler is mechanized combustion equipment with a simple structure and small capacity. Its grate surface vibrates under the action of alternating inertial force and prompts biomass to leap forward on it to achieve mechanized combustion. Burning forest biomass produces heat within the boiler that converts water into steam (steam Rankine cycle). After water evaporation in the boiler, steam enters the turbine to expand and perform work, afterward pressure is reduced, and steam is condensed and converted to water (Dote et al., 2001). It should be noted that the steam Rankine cycle is one of the most critical thermodynamic cycles for electricity generation (Dincer and Bicer, 2020).

The conversion rate of forest biomass into electricity by Rankine cycle is reported at about 39–44%; therefore, the combustion of each ton of forest biomass generates about 4.4 kWh of electric energy (Van den Broek et al., 1996; Dote et al., 2001). One obvious advantage of using this electric energy is reducing fossil-based CO₂ emissions caused by the power generation industry. **Table 2** tabulates the CO₂ emission reductions of forest biomass-based power plants compared to their fossil-based counterparts.

A significant problem with the direct combustion of forest biomass for energy production is that these waste resources are generally far from industrial and residential areas. Moreover, the forests are vast, and biomass collation is a complex problem; thus, lack of permanent access to biomass is a severe concern in the sustainability of direct electricity generation using forest biomass. Nevertheless, it is recommended that forest biomass-based industries be located within a 120 km radius of forests to solve this concern. Still, they need a lot of financial investment and storage capacity (Hoffmann et al., 2012).

Co-combustion of Forest Biomass and Coal

Co-combustion is a feasible and straightforward option for solving the concerns associated with the direct combustion of

forest biomass, such as permanent access to biomass, the area required for storage, and economic problems related to transportation and distribution (Liang et al., 2017). The main advantage of the mixed combustion of biomass and coal vs. coal combustion is that it could reduce carbon monoxide (CO), nitrogen oxides (NO_x), and sulfide emissions while ensuring production efficiency (Perea-Moreno et al., 2017). Technically, the co-combustion of forest biomass and coal uses pulverized coal boiler and fluidized bed boiler as the reactor. In the fluidized bed boiler, when forest biomass is added, the generation of nitric oxide (NO) is reduced, and the combustion process is more efficient (Kabir and Kumar, 2012). Also, compared to coal, the volatile content of biomass is higher that is a favorable parameter for rapid ignition. It has been found that 87 tons of CO₂ emission could be reduced by replacing 1 ton of coal with forest biomass during co-combustion (Royo et al., 2012). It is estimated that in 2030 and beyond, biomass utilization will increase by 450,000 t/yr, and relevant CO₂ emission reduction will reach 395,000 t/yr (Kazagic et al., 2016). Furthermore, alkaline ash caused by biomass combustion can block SO₂ emissions from coal and reduce global acidification (Demirba, 2005; Tsalidis et al., 2014).

Due to reducing harmful gases and increased power generation reliability, co-combustion is considered a cheap option to utilize existing biomass resources in power generation (McIlveen-Wright et al., 2011). Given this fact, thermal power plants can use biomass as clean and cost-effective combustion supporting agent to mix with coal (Dai et al., 2008). However, forest biomass suffers from several significant drawbacks despite these desirable features, e.g., poor energy density, high particle emissions, unstable combustion performance, and difficulties in storage and transportation (Kang et al., 2018). Hence, future research should aim at providing solutions to mitigate these obstacles.

FOREST BIOMASS PELLETS

Several techniques have been developed to facilitate the transportation and improve the conversion rate of forest biomass, like mechanical processing of biomass into granular substance (pellet). Pelletizing of forest biomass improves its density and reduces water content (Valdés et al., 2018). Density and moisture are two critical properties of biomass affecting

combustion efficiency. Hence, direct combustion or co-combustion of pelleted forest biomass with coal could increase combustion efficiency. For instance, it has been reported that the efficiency of pellet-fired boilers ranged between 85 and 90% compared with wood-fired boilers varying from 75 to 85% (Sandro et al., 2019).

Forest biomass can also be mixed with other biomass to enhance the overall properties of the mixture for pellet production (de Souza et al., 2020). For instance, the water content of biomass pellets could affect their durability, a property that could be adjusted by mixing different types of forest biomass. More specifically, when the moisture content of forest biomass is reduced to 1–5%, the average durability reaches 95%, which is convenient for the storage and transportation of the product (Pradhan et al., 2018).

In the manufacturing process of forest biomass pellets, the biomass needs to be dehydrated in advance (Civitarese et al., 2018). A rotary dryer could be used to remove the moisture in poplar wood chips, with a moisture removal rate of about 17%. In comparison, the moisture removal rate for *Robinia pseudoacacia* sawdust stands at a higher rate of 31%. These differences are ascribed to the differences in the density of various types of forest biomass (Prokkola et al., 2014; Del Giudice et al., 2019). Notably, if the rotary dryer cannot remove the moisture effectively, the pneumatic dryer would be a good choice, also increasing the drying rate by 22% (Frodeson et al., 2013).

From an environmental point of view, it is reported that if biomass pellets are used instead of coal for power generation, CO₂ emissions will be reduced by 205 Mt annually (Purohit and Chaturvedi, 2018). Sikkema et al. (2011) reported that through the consumption of 8.2 million tons of wood pellets, 12.6 million tons of CO₂ emissions were avoided in all EU countries in 2008.

Compared with sawdust, coal, and other traditional fuels, mixing forest biomass pellets with coal causes less harm to the environment. For example, co-combustion of forest biomass pellets and coal reportedly led to a 50% reduction in CO₂ emission, and the ash formed in the combustion process only accounted for about 1%, 15–20 times less than coal combustion (Palšauskas and Petkevičius, 2013; Morrison et al., 2018). Ehrig and Behrendt (2013) also showed that co-firing wood pellets with coal resulted in lower CO₂ than other renewables. It is also claimed that adding eggshells in the combustion of forest biomass pellets could also absorb CO₂ through the calcium carbonate present in eggshells, further reducing GHG emissions (Yuan et al., 2019). Molina-Moreno et al. (2016) also reported that CO and NO_x emissions levels caused by pellets combustion were very satisfactory. Tamura et al. (2014) claimed that co-firing wood pellets with coal when wood pellets were burnt in lower row burners could prevent CO emissions.

Despite these promising results, power plants relying on forest biomass pellets also face several problems such as high energy consumption, labor-intensive process, higher prices than other solid biofuels, need for higher storage space in comparison with oil, need for ash removal, and susceptibility of pellets to moisture exposure (Abdoli et al., 2018).

CONVERSION OF FOREST BIOMASS INTO LIQUID BIOFUELS

The pollution caused by diesel combustion in diesel engines is one of the main contributors to global air pollution (Aghbashlo et al., 2017b; 2018b). The most crucial emissions released from diesel combustion are CO₂, NO_x, sulfur oxides (SO_x), CO, and PM emissions (Aghbashlo et al., 2021b). There is evidence that these emissions play a crucial role in damage to the environment and human health (Hosseinzadeh-Bandbafha et al., 2020). To solve the problem associated with diesel exhaust emissions and to mitigate the existing environmental pressure, cleaner alternatives to diesel are widely sought (Khalife et al., 2017; Aghbashlo et al., 2018a).

Biodiesel, long-chain fatty acid methyl or ethyl esters (FAME or FAEE, respectively) is produced mainly *via* the transesterification reaction using short-chain alcohols, i.e., methanol or ethanol, and in the presence of a base or acid catalyst (Chuah et al., 2017; Hajjari et al., 2017). Compared with diesel, biodiesel combustion leads to lower smoke, PM CO, and unburned hydrocarbon (HC) emissions (Amid et al., 2020). Also, it contributes much less to global warming than diesel because the carbon contained in biodiesel is mainly of biogenic CO₂ origin (Hosseinzadeh-Bandbafha et al., 2018). The research on biodiesel production has already reached maturity, resulting in replacing diesel with various biodiesel blends in many parts of the world. It should be noted that neat biodiesel and its blends (up to 20%) with diesel can be used in diesel engines without requiring engine modifications (Narasimharao et al., 2007).

Despite its advantages, some physicochemical properties of biodiesel limit its widespread application, including higher viscosity of biodiesel than fossil diesel and poor cold flow properties (Aghbashlo et al., 2015; Pang, 2019). Moreover, biodiesel production from first-generation feedstock (edible vegetable oils) has led to high production costs and triggered competition between fuel and food over arable land water resources (Aghbashlo et al., 2017a). Fuels derived from waste biomass are classified as second-generation biofuels and are regarded as a solution to overcome the mentioned competition between food and fuel (Laesecke et al., 2017). High oil content tree species are suitable raw materials for biodiesel production (Patel et al., 2019).

Pyrolysis is also a promising thermochemical valorization technique for producing biofuels from forest waste at moderate temperatures (typically between 300 and 1,300°C) (Aghbashlo et al., 2019; Yek et al., 2020). During this process, the feedstock's chemical structure faces fundamental changes (Foong et al., 2020; Ge et al., 2021). Generally, pyrolysis is known as the method with the ability to produce a variety of solid, liquid, and gaseous products depending on pyrolysis conditions (Aghbashlo et al., 2021a). Slow pyrolysis produces solid products such as biochar or charcoal, while fast pyrolysis results in the production of liquid products (bio-oil). It is reported that forest biomass is an ideal feedstock for pyrolysis (Chireshe et al., 2020), and different researchers have successfully conducted pyrolysis of forest biomass to produce bio-oil (Oasmaa et al., 2010; Puy et al., 2011; Stefanidis et al., 2015; Luo et al., 2017). It should be

TABLE 3 | Potential of different types of forest biomass for second-generation bioethanol production.

Biomass species	Convertible materials (%)	Convertible materials yield (t/ha/yr)	Potential bioethanol yield (L/ha)	References
<i>Manihot esculenta</i>	35 (Sugar)	30	4,500–4,901	Zabed et al. (2016)
<i>Miscanthus</i> spp.	56–73.5 (Holocellulose)	5–43	4,600–12,400	Ho et al. (2014)
<i>Panicum virgatum</i>	35–70 (Holocellulose)	5–25	555–3,871	Zabed et al. (2016)
<i>Populus</i> spp.	56 (Holocellulose)	2–10	1,500–3,400	Ho et al. (2014)
<i>Saccharum</i> spp.	12–17.6 (Sugar)	70–122.9 (Sugar)	5,345–9,950	Lebaka (2013)
	61–73 (Holocellulose)	19.6–34.4 (Holocellulose)		
<i>Salix</i> spp.	69.9 (Holocellulose)	5–11	769–4,026	Zamora et al. (2014)
<i>Triticum aestivum</i>	65.3–76 (Sugar)	1.8–6.4 (Sugar)	1,001–1700	Lebaka (2013)
	59–70 (Holocellulose)	6.5–11 (Holocellulose)		

noted that the bio-oil produced by the pyrolysis process typically has a high oxygen and water content, and thus, it should be upgraded (van Schalkwyk et al., 2020).

Another conversion pathway to valorize forest biomass is gasification. González and García (2015) converted wood biomass into bio-oil through the gasification process and subsequent liquefaction (Fischer-Tropsch). Natarajan et al. (2014) reported that the installation of five Fischer-Tropsch plants could contribute to achieving Finland's various 2020 targets, i.e., using up to 58% of the available forest biomass for energy production, total emission reduction of 4%, and powering the transportation sector with 100% biofuel. Sunde et al. (2011) also estimated that converting forest biomass and woody wastes into liquid biofuel by the Fischer-Tropsch process as a replacement for fossil diesel could reduce the overall environmental impacts of the transportation sector in Norway. GHG savings and reductions in greenhouse impacts by production and use of Fischer-Tropsch biofuel from forest residues are estimated to amount to roughly 20–90% on a 100-year timescale (Jäppinen et al., 2014). It should also be noted that in addition to reducing CO₂ emissions, biofuel production from forest biomass could also offer economic opportunities, including creating new jobs (Natarajan et al., 2014).

Bioethanol production from forest biomass has also been investigated since the early 1990s (Mabee and Saddler, 2010). The lignocellulosic nature of forest biomass (such as *Populus*L., *Salix babylonica*, and *Saccharum officinarum*) and its abundance mark it as a suitable feedstock for second-generation bioethanol production (Limayem and Rieke, 2012; Ko et al., 2020). International Energy Agency (IEA) estimates that the potential use of 10% of global forest and agricultural biomass in 2030 can provide 233 billion L of bioethanol, equivalent to 155 billion L of gasoline (Morales et al., 2021). The bioethanol production potentials of several forest biomass are shown in Table 3.

Bioethanol is well known as a promising substitute for petroleum-based gasoline (Huang et al., 2020; Amid et al., 2021), with considerably lower emissions throughout its life cycle (Mabee and Saddler, 2010). For example, Becerra-Ruiz et al. (2019) reported a decrease of 99, 93, and 67% in CO, HC, and NO_x, respectively, when a 5500 W portable engine generator of alternating current burned bioethanol instead of gasoline. Compared to first-generation bioethanol such as corn and sugarcane-based bioethanol, second-generation bioethanol (i.e., bioethanol produced from lignocellulosic feedstocks) has

significantly lower life cycle GHG emissions (Wang et al., 2020). Moreover, bioethanol yields of forest biomass are relatively higher than those of other types of biomass. In a study investigating bioethanol yields, Mabee and Saddler (2010) reported that bioethanol yields of forest biomass ranged between 0.12 and 0.3 m³/t (dry basis) vs. 0.11 and 0.27 m³/t (dry basis) for bioethanol production from agricultural residues.

The biochemical or thermochemical conversion are two primary methods used to process lignocellulosic feedstocks into bioethanol (Soltanian et al., 2020). The biochemical conversion starts with pretreatment to separate hemicellulose and lignin from cellulose and is followed by hydrolysis of cellulose to obtain fermentable sugars (Panahi et al., 2020a). Finally, sugars are fermented into ethanol (Anyanwu et al., 2018). Pretreatment is an instrumental stage of the process, and hence, its type and conditions play important roles in the overall technical viability of the whole process (Negro et al., 2020; Morales et al., 2021). The various pretreatment methods include chemical, physical, physicochemical, and biological (Sharma et al., 2020).

It should be noted that forest biomass, due to the presence of bark and juvenile wood, tends to have higher lignin contents (Zhu et al., 2015). As a result, forest biomass is more recalcitrant to bioconversion into sugars than other biomass types such as agricultural residues (Yamamoto et al., 2014). Although there are pretreatment processes to overcome such a high level of recalcitrance for efficient sugar/biofuel production, they are more time-consuming and costlier. One of these methods is steam explosion treatment which has been reported to increase bioethanol production of *Hemp fiber* by upto 70% (Zhao et al., 2020). It has also been claimed that the application of surfactants, owing to their unique structure and functional properties, could improve the solubility, fluidity, bioavailability, and biodegradability of forest biomass, thereby increasing the production of bioethanol. Zheng et al. (2020) argued that tween, polyethylene glycol (PEG), and sulfonate-based surfactants could increase the conversion rate of lignocellulose by 10–20%.

Compared to the biochemical conversion, thermochemical conversion, particularly gasification, can be applied to a broader range of forest biomass (Wang et al., 2020). During gasification of the lignocellulosic biomass at high pressure and in the absence of inert gases, lignocellulosic biomass is converted into syngas, which will then be converted into bioethanol through the Fischer-Tropsch process (Laesecke et al., 2017). Also, syngas can be

utilized by the microorganism *Clostridium ljungdahlii* to generate bioethanol in the presence of catalysts (Limayem and Ricke, 2012).

CONVERSION OF FOREST BIOMASS INTO GASEOUS BIOFUELS

The gasification process of forest biomass leads to syngas production through a series of thermal cracking reactions (Burbano et al., 2011). Forest biomass, including seeds, leaves, tree trunks, and fruit shells, could be pyrolyzed in a fixed bed gasifier for a long time at high temperatures (above 1,200°C) to produce hydrogen-rich syngas (Brachi et al., 2014; Ozbas et al., 2019), which has been highlighted as one of the most promising alternative sources of energy (Shih and Hsu, 2011). It is claimed that 1.3 Gt/yr of biomass can produce 100 Mt/yr of hydrogen (Duan et al., 2020).

During gasification, the reaction rate can be controlled by adjusting the gas flow. Using this strategy, the decomposition rate of forest biomass into hydrogen could reach 60% (Solar et al., 2018). The cost of hydrogen production from forest biomass through gasification is about 1.18 USD/kg H₂ (Sarkar and Kumar, 2009), almost half of the other processes (Sarkar and Kumar, 2010). It should be noted that industrial gasification devices are usually connected with power generation equipment to generate electricity while providing gas; the former can be supplied to nearby households (Sasujit et al., 2017; Schulzke, 2019).

Adding appropriate catalysts to the gasification process can improve the gas content (Pang, 2019). In the catalytic gasification experiment of *Eucalyptus* residue with NiO as the catalyst, the total gas production increased by 30%. Corujo et al (2010) also reported that through catalytic gasification, the biochar and ash contents were decreased, and the utilization rate of biomass was improved. It has been argued that catalytic cracking is more economical than traditional biofuel production methods such as pyrolysis and fermentation (Meerman and Larson, 2017).

In addition to producing hydrogen-rich syngas, forest biomass can also be used to produce biogas through anaerobic digestion (Tabatabaei et al., 2020a). The technology of converting forest biomass into CH₄ is relatively mature and has been used for practical production for many years (González et al., 2006; Tabatabaei et al., 2020b). The production of biogas, whose main components are CH₄ and CO₂, is largely affected by the composition of raw materials (Dehghani et al., 2019). It should be noted that in addition to species, the composition of forest biomass could also be affected by variations in geographical location and growth environment.

One of the main challenges of anaerobic digestion is the non-degradability of lignin under anaerobic conditions (Dehghani et al., 2019). In better words, lignocellulose-rich organic materials such as forest biomass suffer from the disadvantage of low availability of cellulose and hemicellulose as biodegradable components for microorganisms and their enzymes (López et al., 2013). Nevertheless, similar to other types of lignocellulosic biomass, chemical (hydrolysis with acids, alkali, or oxidants), physical (irradiation, shredding, thermal, and pressure shocks), and biological (fungi, actinobacteria, or their enzymes) pretreatments could also be employed to improve the anaerobic

biodegradation of forest biomass (Chang and Holtzapple, 2000; Taherzadeh and Karimi, 2008; Hendriks and Zeeman, 2009).

CONCLUSION

It was shown that forest biomass could, directly and indirectly, be used as an energy resource. More specifically, forest biomass can be directly combusted to reduce CO₂ emissions associated with conventional energy production processes. However, the energy conversion rate of forest biomass is low, and it also leads to emissions of soot and residues. Also, the lack of continuous access to biomass and the need for lots of financial investment and storage capacity are among the severe concerns in the sustainability of direct electricity generation using forest biomass.

In comparison, co-combustion of biomass and coal vs. combustion of coal alone could be regarded as a promising strategy to reduce emissions while ensuring production efficiency. It also partly solves issues related to biomass availability, the area required for storage, and economic problems related to transportation and distribution. Despite these desirable features, forest biomass suffers from poor energy density and high moisture, which could be addressed by pelleting forest biomass. Due to the improved density and moisture, direct combustion of pelleted forest biomass or its co-combustion with coal accelerates the combustion rate. Nevertheless, power plants relying on forest biomass pellets also face several problems such as high energy consumption, labor-intensive process, and higher prices than other solid biofuels. Forest biomass also can be converted into bio-oil, bioethanol, and biogas by biochemical and thermochemical methods, which are critically explained in the present work.

Given the growing awareness about the environmental consequences of burning fossil fuels, the future will undoubtedly shift toward the use of more biomass and biofuels. Although forest biomass conversion processes to bioenergy are well known, as mentioned, their long-term sustainability should be more extensively scrutinized by future studies using advanced sustainability assessment tools such as life cycle assessment, exergy, etc.

AUTHOR CONTRIBUTIONS

All authors listed have made a substantial, direct, and intellectual contribution to the work and approved it for publication.

FUNDING

The article is supported by the Program for Innovative Research Team (in Science and Technology) in University of Henan Province (No. 21IRTSTHN020) and Central Plain Scholar Funding Project of Henan Province (No. 212101510005).

CORRECTION NOTE

A correction has been made to this article. Details can be found at: 10.3389/fenrg.2025.1731047.

REFERENCES

- Abdoli, M. A., Golzary, A., Hosseini, A., and Sadeghi, P. (2018). "Wood Pellet," in *Wood Pellet As a Renewable Source Of Energy* (Springer), 47–60. doi:10.1007/978-3-319-74482-7_3
- Aghbashlo, M., Tabatabaei, M., Mohammadi, P., Pourvosoughi, N., Nikbakht, A. M., and Goli, S. A. H. (2015). Improving Exergetic and Sustainability Parameters of a DI Diesel Engine Using Polymer Waste Dissolved in Biodiesel as a Novel Diesel Additive. *Energy Convers. Manag.* 105, 28–337. doi:10.1016/j.enconman.2015.07.075
- Aghbashlo, M., Hosseinpour, S., Tabatabaei, M., and Dadak, A. (2017a). Fuzzy Modeling and Optimization of the Synthesis of Biodiesel from Waste Cooking Oil (WCO) by a Low Power, High Frequency Piezo-Ultrasonic Reactor. *Energy* 132, 65–78. doi:10.1016/j.energy.2017.05.041
- Aghbashlo, M., Tabatabaei, M., Mohammadi, P., Khoshnevisan, B., Rajaifar, M. A., and Pakzad, M. (2017b). Neat Diesel Beats Waste-Oriented Biodiesel from the Exergoeconomic and Exergoenvironmental point of Views. *Energy Convers. Manage.* 148, 1–15. doi:10.1016/j.enconman.2017.05.048
- Aghbashlo, M., Tabatabaei, M., and Hosseinpour, S. (2018a). On the Exergoeconomic and Exergoenvironmental Evaluation and Optimization of Biodiesel Synthesis from Waste Cooking Oil (WCO) Using a Low Power, High Frequency Ultrasonic Reactor. *Energy Convers. Manage.* 164, 385–398. doi:10.1016/j.enconman.2018.02.086
- Aghbashlo, M., Tabatabaei, M., Khalife, E., Roodbar Shojai, T., and Dadak, A. (2018b). Exergoeconomic Analysis of a DI Diesel Engine Fueled with Diesel/biodiesel (B5) Emulsions Containing Aqueous Nano Cerium Oxide. *Energy* 149, 967–978. doi:10.1016/j.energy.2018.02.082
- Aghbashlo, M., Tabatabaei, M., Nadian, M. H., Davoodnia, V., and Soltanian, S. (2019). Prognostication of Lignocellulosic Biomass Pyrolysis Behavior Using ANFIS Model Tuned by PSO Algorithm. *Fuel* 253, 189–198. doi:10.1016/j.fuel.2019.04.169
- Aghbashlo, M., Almasi, F., Jafari, A., Nadian, M. H., Soltanian, S., Lam, S. S., et al. (2021a). Describing Biomass Pyrolysis Kinetics Using a Generic Hybrid Intelligent Model: A Critical Stage in Sustainable Waste-Oriented Biorefineries. *Renew. Energy* 170, 81–91. doi:10.1016/j.renene.2021.01.111
- Aghbashlo, M., Peng, W., Tabatabaei, M., Kalogirou, S. A., Soltanian, S., Hosseinzadeh-Bandbafha, H., et al. (2021b). Machine Learning Technology in Biodiesel Research: A Review. *Prog. Energy Combustion Sci.* 85, 100904. doi:10.1016/j.pecs.2021.100904
- Amid, S., Aghbashlo, M., Tabatabaei, M., Hajiahmad, A., Najafi, B., Ghaziaskar, H. S., et al. (2020). Effects of Waste-Derived Ethylene Glycol Diacetate as a Novel Oxygenated Additive on Performance and Emission Characteristics of a Diesel Engine Fueled with Diesel/biodiesel Blends. *Energy Convers. Manage.* 203, 112245. doi:10.1016/j.enconman.2019.112245
- Amid, S., Aghbashlo, M., Tabatabaei, M., Karimi, K., Nizami, A.-S., Rehan, M., et al. (2021). Exergetic, Exergoeconomic, and Exergoenvironmental Aspects of an Industrial-Scale Molasses-Based Ethanol Production Plant. *Energy Convers. Manage.* 227, 113637. doi:10.1016/j.enconman.2020.113637
- Anyanwu, R., Rodriguez, C., Durrant, A., and Olabi, A.-G. (2018). "Micro-macroalgae Properties and Applications," In *Reference Module In Materials Science And Materials Engineering*. Elsevier BV. doi:10.1016/b978-0-12-803581-8.09259-6
- Becerra-Ruiz, J. D., Gonzalez-Huerta, R. G., Gracida, J., Amaro-Reyes, A., and Macias-Bobadilla, G. (2019). Using green-hydrogen and Bioethanol Fuels in Internal Combustion Engines to Reduce Emissions. *Int. J. Hydrogen Energy* 44, 12324–12332. doi:10.1016/j.ijhydene.2019.02.211
- Böttcher, H., and Graichen, J. (2015). Impacts on the EU 2030 Climate Target of Including LULUCF in the Climate and Energy Policy Framework. Available at: <http://www.oeko.de/oekodoc/2320/2015-491-en.pdf> (Accessed June 25, 2020).
- Brachi, P., Chirone, R., Miccio, F., Miccio, M., Picarelli, A., and Ruoppolo, G. (2014). Fluidized Bed Co-gasification of Biomass and Polymeric Wastes for a Flexible End-Use of the Syngas: Focus on Bio-Methanol. *Fuel* 128, 88–98. doi:10.1016/j.fuel.2014.02.070
- Burbano, H. J., Pareja, J., and Amell, A. A. (2011). Laminar Burning Velocities and Flame Stability Analysis of H₂/CO/air Mixtures with Dilution of N₂ and CO₂. *Int. J. Hydrogen Energy* 36, 3232–3242. doi:10.1016/j.ijhydene.2010.11.089
- Calvo, A. I., Tarelho, L. A. C., Teixeira, E. R., Alves, C., Nunes, T., Duarte, M., et al. (2013). Particulate Emissions from the Co-combustion of forest Biomass and Sewage Sludge in a Bubbling Fluidised Bed Reactor. *Fuel Process. Technol.* 114, 58–68. doi:10.1016/j.fuproc.2013.03.021
- Campbell, N., and Mika, A. (2009). VCC Report - Evaluating Potential Uses of Vermont's Wood Biomass for Greenhouse Gas Mitigation. Available at: <https://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.580.8954&rep=rep1&type=pdf> (Accessed June 25, 2021).
- Chang, V. S., and Holtzapple, M. T. (2000). "Fundamental Factors Affecting Biomass Enzymatic Reactivity," in *Twenty-first Symposium on Biotechnology for Fuels and Chemicals* (Springer), 5–37. doi:10.1007/978-1-4612-1392-5_1
- Chen, H., Xue, K., Wu, Y., Xu, G., Jin, X., and Liu, W. (2021). Thermodynamic and Economic Analyses of a Solar-Aided Biomass-Fired Combined Heat and Power System. *Energy* 214, 119023. doi:10.1016/j.energy.2020.119023
- Chireshe, F., Collard, F.-X., and Görgens, J. F. (2020). Production of Low Oxygen Bio-Oil via Catalytic Pyrolysis of forest Residues in a Kilogram-Scale Rotary kiln Reactor. *J. Clean. Prod.* 260, 120987. doi:10.1016/j.jclepro.2020.120987
- Chuah, L. F., Klemesš, J. J., Yusup, S., Bokhari, A., and Akbar, M. M. (2017). A Review of Cleaner Intensification Technologies in Biodiesel Production. *J. Clean. Prod.* 146, 181–193. doi:10.1016/j.jclepro.2016.05.017
- Civitaresse, V., Faugno, S., Picchio, R., Assirelli, A., Sperandio, G., Saulino, L., et al. (2018). Production of Selected Short-Rotation wood Crop Species and Quality of Obtained Biomass. *Eur. J. For. Res* 137, 541–552. doi:10.1007/s10342-018-1122-3
- Corujo, A., Yermán, L., Arizaga, B., Brusoni, M., and Castiglioni, J. (2010). Improved Yield Parameters in Catalytic Steam Gasification of Forestry Residue; Optimizing Biomass Feed Rate and Catalyst Type. *Biomass Bioenergy* 34, 1695–1702. doi:10.1016/j.biombioe.2010.06.010
- Dai, J., Sokhansanj, S., Grace, J. R., Bi, X., Lim, C. J., and Melin, S. (2008). Overview and Some Issues Related to Co-firing Biomass and Coal. *Can. J. Chem. Eng.* 86, 367–386. doi:10.1002/cjce.20052
- de Souza, H. J. P. L., Arantes, M. D. C., Vidaurre, G. B., Andrade, C. R., Carneiro, A. d. C. O., de Souza, D. P. L., et al. (2020). Pelletization of eucalyptus wood and Coffee Growing Wastes: Strategies for Biomass Valorization and Sustainable Bioenergy Production. *Renew. Energy* 149, 128–140. doi:10.1016/j.renene.2019.12.015
- Dehghani, M., Tabatabaei, M., Aghbashlo, M., Kazemi Shariat Panahi, H., and Nizami, A.-S. (2019). A State-Of-The-Art Review on the Application of Nanomaterials for Enhancing Biogas Production. *J. Environ. Manage.* 251, 109597. doi:10.1016/j.jenvman.2019.109597
- Del Giudice, A., Acampora, A., Santangelo, E., Pari, L., Bergonzoli, S., Guerriero, E., et al. (2019). Wood Chip Drying through the Using of a mobile Rotary Dryer. *Energies* 12, 1590. doi:10.3390/en12091590
- Demirba, A. (2005). Influence of Gas and Detrimental Metal Emissions from Biomass Firing and Co-firing on Environmental Impact. *Energy Sourc.* 27, 1419–1428. doi:10.1080/009083190523271
- Dincer, I., and Bicer, Y. (2020). "Fundamentals of Energy Systems," in *Fundamentals of Energy Systems, Integrated Energy Systems for Multigeneration* (Amsterdam, Netherlands: Elsevier), 33–83.
- Dote, Y., Ogi, T., and Yokoyama, S. (2001). "Estimate of the Net CO₂ Reduction by Replacing Coal and Oil with Biomass in Japan," in *Progress in Thermochemical Biomass Conversion* (Hoboken, New Jersey: John Wiley & Sons), 956–963.
- Duan, Y., Pandey, A., Zhang, Z., Awasthi, M. K., Bhatia, S. K., and Taherzadeh, M. J. (2020). Organic Solid Waste Biorefinery: Sustainable Strategy for Emerging Circular Bioeconomy in China. *Ind. Crops Prod.* 153, 112568. doi:10.1016/j.indcrop.2020.112568
- Ehrig, R., and Behrendt, F. (2013). Co-firing of Imported wood Pellets - an Option to Efficiently Save CO₂ Emissions in Europe? *Energy Policy* 59, 283–300. doi:10.1016/j.enpol.2013.03.060
- Foong, S. Y., Liew, R. K., Yang, Y., Cheng, Y. W., Yek, P. N. Y., Wan Mahari, W. A., et al. (2020). Valorization of Biomass Waste to Engineered Activated Biochar by Microwave Pyrolysis: Progress, Challenges, and Future Directions. *Chem. Eng. J.* 389, 124401. doi:10.1016/j.cej.2020.124401
- Frodeson, S., Berghel, J., and Renström, R. (2013). The Potential of Using Two-step Drying Techniques for Improving Energy Efficiency and Increasing Drying Capacity in Fuel Pellet Industries. *Drying Technol.* 31, 1863–1870. doi:10.1080/07373937.2013.833520

- Froese, R. E., Shonnard, D. R., Miller, C. A., Koers, K. P., and Johnson, D. M. (2010). An Evaluation of Greenhouse Gas Mitigation Options for Coal-Fired Power Plants in the US Great Lakes States. *Biomass Bioenergy* 34, 251–262. doi:10.1016/j.biombioe.2009.10.013
- Furubayashi, T., and Nakata, T. (2018). Cost and CO₂ Reduction of Biomass Co-Firing Using Waste Wood Biomass in Tohoku Region, Japan. *J. Clean. Prod.* 174, 1044–1053.
- Ge, S., Yek, P. N. Y., Cheng, Y. W., Xia, C., Mahari, W. A. W., Liew, R. K., et al. (2021). Progress in Microwave Pyrolysis Conversion of Agricultural Waste to Value-Added Biofuels: A Batch to Continuous Approach. *Renew. Sustain. Energy Rev.* 135, 110148. doi:10.1016/j.rser.2020.110148
- González, J. F., Gañán, J., Ramiro, A., González-García, C. M., Encinar, J. M., Sabio, E., et al. (2006). Almond Residues Gasification Plant for Generation of Electric Power. Preliminary Study. *Fuel Process. Technol.* 87, 149–155. doi:10.1016/j.fuproc.2005.08.010
- González, J., and García, A. (2015). Availability of forest Biomass in Chile for Second Generation Biodiesel Production. *International Congress of Energy and Environment Engineering and Management*.
- Gustavsson, L., Haus, S., Ortiz, C. A., Sathre, R., and Truong, N. L. (2015). Climate Effects of Bioenergy from forest Residues in Comparison to Fossil Energy. *Appl. Energy* 138, 36–50. doi:10.1016/j.apenergy.2014.10.013
- Hajjari, M., Tabatabaei, M., Aghbashlo, M., and Ghanavati, H. (2017). A Review on the Prospects of Sustainable Biodiesel Production: A Global Scenario with an Emphasis on Waste-Oil Biodiesel Utilization. *Renew. Sustain. Energy Rev.* 72, 445–464. doi:10.1016/j.rser.2017.01.034
- Hendriks, A. T. W. M., and Zeeman, G. (2009). Pretreatments to Enhance the Digestibility of Lignocellulosic Biomass. *Bioresour. Technol.* 100, 10–18. doi:10.1016/j.biortech.2008.05.027
- Ho, D. P., Ngo, H. H., and Guo, W. (2014). A Mini Review on Renewable Sources for Biofuel. *Bioresour. Technol.* 169, 742–749. doi:10.1016/j.biortech.2014.07.022
- Hoffmann, B. S., Szklo, A., and Schaeffer, R. (2012). An Evaluation of the Techno-Economic Potential of Co-firing Coal with Woody Biomass in thermal Power Plants in the South of Brazil. *Biomass Bioenergy* 45, 295–302. doi:10.1016/j.biombioe.2012.06.016
- Hong-ru, M., and Yi-hu, S. (2007). Study on Direct-Combustion Technology of Biomass [J]. *J. Agric. Mech. Res.* 8.
- Hosseinizadeh-Bandbafha, H., Tabatabaei, M., Aghbashlo, M., Khanali, M., and Demirbas, A. (2018). A Comprehensive Review on the Environmental Impacts of Diesel/biodiesel Additives. *Energy Convers. Manage.* 174, 579–614. doi:10.1016/j.enconman.2018.08.050
- Hosseinizadeh-Bandbafha, H., Tabatabaei, M., Aghbashlo, M., Khanali, M., Khalife, E., Roodbar Shojaei, T., et al. (2020). Consolidating Emission Indices of a Diesel Engine Powered by Carbon Nanoparticle-Doped Diesel/biodiesel Emulsion Fuels Using Life Cycle Assessment Framework. *Fuel* 267, 117296. doi:10.1016/j.fuel.2020.117296
- Huang, C., Fang, G., Yu, L., Zhou, Y., Meng, X., Deng, Y., et al. (2020). Maximizing Enzymatic Hydrolysis Efficiency of Bamboo with a Mild Ethanol-Assistant Alkaline Peroxide Pretreatment. *Bioresour. Technol.* 299, 122568. doi:10.1016/j.biortech.2019.122568
- Ince, P. J., Kramp, A. D., Skog, K. E., Yoo, D.-i., and Sample, V. A. (2011). Modeling Future U.S. forest Sector Market and Trade Impacts of Expansion in wood Energy Consumption. *Jfe* 17, 142–156. doi:10.1016/j.jfe.2011.02.007
- Jäppinen, E., Korpinen, O.-J., and Ranta, T. (2014). GHG Emissions of forest-biomass Supply Chains to Commercial-Scale Liquid-Biofuel Production Plants in Finland. *Gcb Bioenergy* 6, 290–299. doi:10.1111/gcbb.12048
- Jun-jun, L., and Da-rui, W. (2012). Considerations about Developing Future Energy. *Oil Forum* 4.
- Kabir, M. R., and Kumar, A. (2012). Comparison of the Energy and Environmental Performances of Nine Biomass/coal Co-firing Pathways. *Bioresour. Technol.* 124, 394–405. doi:10.1016/j.biortech.2012.07.106
- Kacprzak, A., Kobyłcki, R., Włodarczyk, R., and Bis, Z. (2016). Efficiency of Non-optimized Direct Carbon Fuel Cell with Molten Alkaline Electrolyte Fueled by Carbonized Biomass. *J. Power Sourc.* 321, 233–240. doi:10.1016/j.jpowsour.2016.04.132
- Kang, K., Zhu, M., Sun, G., Qiu, L., Guo, X., Meda, V., et al. (2018). Codensification of *Eucommia Ulmoides* Oliver Stem with Pyrolysis Oil and Char for Solid Biofuel: An Optimization and Characterization Study. *Appl. Energy* 223, 347–357. doi:10.1016/j.apenergy.2018.04.069
- Karaj, S., Rehl, T., Leis, H., and Müller, J. (2010). Analysis of Biomass Residues Potential for Electrical Energy Generation in Albania. *Renew. Sustain. Energy Rev.* 14, 493–499. doi:10.1016/j.rser.2009.07.026
- Kazagic, A., Music, M., Smajevic, I., Ademovic, A., and Redzic, E. (2016). Possibilities and Sustainability of “biomass for Power” Solutions in the Case of a Coal-Based Power Utility. *Clean. Techn Environ. Pol.* 18, 1675–1683. doi:10.1007/s10098-016-1193-0
- Khalife, E., Tabatabaei, M., Demirbas, A., and Aghbashlo, M. (2017). Impacts of Additives on Performance and Emission Characteristics of Diesel Engines during Steady State Operation. *Prog. Energy Combustion Sci.* 59, 32–78. doi:10.1016/j.pecs.2016.10.001
- Ko, J. K., Lee, J. H., Jung, J. H., and Lee, S.-M. (2020). Recent Advances and Future Directions in Plant and Yeast Engineering to Improve Lignocellulosic Biofuel Production. *Renew. Sustain. Energy Rev.* 134, 110390. doi:10.1016/j.rser.2020.110390
- Laescke, J., Ellis, N., and Kirchen, P. (2017). Production, Analysis and Combustion Characterization of Biomass Fast Pyrolysis Oil - Biodiesel Blends for Use in Diesel Engines. *Fuel* 199, 346–357. doi:10.1016/j.fuel.2017.01.093
- Lam, M. K., Loy, A. C. M., Yusup, S., and Lee, K. T. (2019). “Biohydrogen Production from Algae,” in *Biohydrogen*. Elsevier, 219–245. doi:10.1016/b978-0-444-64203-5.00009-5
- Lebaka, V. R. (2013). “Potential Bioresources as Future Sources of Biofuels Production: An Overview,” in *Biofuel Technologies: Recent Developments* (Berlin, Heidelberg: Springer).
- Liang, F., Wang, R., Jiang, C., Yang, X., Zhang, T., Hu, W., et al. (2017). Investigating Co-combustion Characteristics of Bamboo and wood. *Bioresour. Technol.* 243, 556–565. doi:10.1016/j.biortech.2017.07.003
- Liao, C., Wu, C., and Huang, H. (2004). Study on the Distribution and Quantity of Biomass Residues Resource in China. *Biomass Bioenergy* 27, 111–117. doi:10.1016/j.biombioe.2003.10.009
- Limayem, A., and Ricke, S. C. (2012). Lignocellulosic Biomass for Bioethanol Production: Current Perspectives, Potential Issues and Future Prospects. *Prog. Energy Combustion Sci.* 38, 449–467. doi:10.1016/j.pecs.2012.03.002
- López, M., Suárez-Estrella, F., Vargas-García, M. C., López-González, J. A., Verstichel, S., Debeer, L., et al. (2013). Biodelignification of Agricultural and forest Wastes: Effect on Anaerobic Digestion. *Biomass bioenergy* 58, 343–349. doi:10.1016/j.biombioe.2013.10.021
- Luo, G., Chandler, D. S., Anjos, L. C. A., Eng, R. J., Jia, P., and Resende, F. L. P. (2017). Pyrolysis of Whole wood Chips and Rods in a Novel Ablative Reactor. *Fuel* 194, 229–238. doi:10.1016/j.fuel.2017.01.010
- Mabee, W. E., and Saddler, J. N. (2010). Bioethanol from Lignocellulosics: Status and Perspectives in Canada. *Bioresour. Technol.* 101, 4806–4813. doi:10.1016/j.biortech.2009.10.098
- Mallaki, M., and Fatehi, R. (2014). Design of a Biomass Power Plant for Burning Date Palm Waste to Cogenerate Electricity and Distilled Water. *Renew. Energy* 63, 286–291.
- McIlveen-Wright, D. R., Huang, Y., Rezvani, S., Mondol, J. D., Redpath, D., Anderson, M., et al. (2011). A Techno-Economic Assessment of the Reduction of Carbon Dioxide Emissions through the Use of Biomass Co-combustion☆. *Fuel* 90, 11–18. doi:10.1016/j.fuel.2010.08.022
- Meerman, J. C., and Larson, E. D. (2017). Negative-carbon Drop-In Transport Fuels Produced via Catalytic Hydrolysis of Woody Biomass with CO₂ capture and Storage. *Sustain. Energy Fuels* 1, 866–881. doi:10.1039/c7se00013h
- Moiseyev, A., Solberg, B., and Kallio, A. M. I. (2014). The Impact of Subsidies and Carbon Pricing on the wood Biomass Use for Energy in the EU. *Energy* 76, 161–167. doi:10.1016/j.energy.2014.05.051
- Molina-Moreno, V., Leyva-Díaz, J., and Sánchez-Molina, J. (2016). Pellet as a Technological Nutrient within the Circular Economy Model: Comparative Analysis of Combustion Efficiency and CO and NO_x Emissions for Pellets from Olive and almond Trees. *Energies* 9, 777. doi:10.3390/en9100777
- Morales, M., Arvesen, A., and Cherubini, F. (2021). Integrated Process Simulation for Bioethanol Production: Effects of Varying Lignocellulosic Feedstocks on Technical Performance. *Bioresour. Technol.* 328, 124833. doi:10.1016/j.biortech.2021.124833

- Morrison, B., Daystar, J., and Golden, J. S. (2018). Substituting wood Pellets for Coal in Large-Scale Power Stations: a Dynamic Life Cycle Assessment Examination. *Ijgei* 41, 272–288. doi:10.1504/ijgei.2018.10018219
- Nakano, S., Murano, A., and Washizu, A. (2015). Economic and Environmental Effects of Utilizing Unused Woody Biomass. *J. Japan Inst. Energy* 94, 522–531.
- Narasimharao, K., Lee, A., and Wilson, K. (2007). Catalysts in Production of Biodiesel: a Review. *J. biobased mat bioenergy* 1, 19–30. doi:10.1166/jbmb.2007.1976
- Natarajan, K., Leduc, S., Pelkonen, P., Tomppo, E., and Dotzauer, E. (2014). Optimal Locations for Second Generation Fischer Tropsch Biodiesel Production in Finland. *Renew. Energy* 62, 319–330. doi:10.1016/j.renene.2013.07.013
- Negro, M. J., Álvarez, C., Doménech, P., Iglesias, R., and Ballesteros, I. (2020). Sugars Production from Municipal Forestry and Greening Wastes Pretreated by an Integrated Steam Explosion-Based Process. *Energies* 13, 4432. doi:10.3390/en13174432
- Nunes, L. J. R., Matias, J. C. O., and Catalão, J. P. S. (2014). A Review on Torrefied Biomass Pellets as a Sustainable Alternative to Coal in Power Generation. *Renew. Sustain. Energy Rev.* 40, 153–160.
- Nunes, L. J. R., Godina, R., Matias, J. C. O., and Catalão, J. P. S. (2018). Economic and Environmental Benefits of Using Textile Waste for the Production of thermal Energy. *J. Clean. Prod.* 171, 1353–1360. doi:10.1016/j.jclepro.2017.10.154
- Oasmaa, A., Solantausta, Y., Arpiainen, V., Kuoppala, E., and Sipilä, K. (2010). Fast Pyrolysis Bio-Oils from wood and Agricultural Residues. *Energy Fuels* 24, 1380–1388. doi:10.1021/ef901107f
- Ozbas, E. E., Aksu, D., Ongen, A., Aydin, M. A., and Ozcan, H. K. (2019). Hydrogen Production via Biomass Gasification, and Modeling by Supervised Machine Learning Algorithms. *Int. J. Hydrogen Energy* 44, 17260–17268. doi:10.1016/j.ijhydene.2019.02.108
- Palšauskas, M. ys., and Petkevičius, S. (2013). A New Approach to Renewable Energy: New Mixed Biomass Pellets. *J. Food Agric. Environ.* 11, 798–802.
- Panahi, H. K. S., Dehghani, M., Aghbashlo, M., Karimi, K., and Tabatabaei, M. (2020a). Conversion of Residues from Agro-Food Industry into Bioethanol in Iran: An Under-valued Biofuel Additive to Phase Out MTBE in Gasoline. *Renew. Energy* 145, 699–710. doi:10.1016/j.renene.2019.06.081
- Panahi, H. K. S., Dehghani, M., Ok, Y. S., Nizami, A.-S., Khoshnevisan, B., Mussatto, S. I., et al. (2020b). A Comprehensive Review of Engineered Biochar: Production, Characteristics, and Environmental Applications. *J. Clean. Prod.* 270, 122462. doi:10.1016/j.jclepro.2020.122462
- Pang, S. (2019). Advances in Thermochemical Conversion of Woody Biomass to Energy, Fuels and Chemicals. *Biotechnol. Adv.* 37, 589–597. doi:10.1016/j.biotechadv.2018.11.004
- Patel, M., Oyedun, A. O., Kumar, A., and Gupta, R. (2019). What is the Production Cost of Renewable Diesel from Woody Biomass and Agricultural Residue Based on Experimentation? A Comparative Assessment. *Fuel Process. Technol.* 191, 79–92.
- Perea-Moreno, A.-J., Perea-Moreno, M.-Á., Hernandez-Escobedo, Q., and Manzano-Agugliaro, F. (2017). Towards forest Sustainability in Mediterranean Countries Using Biomass as Fuel for Heating. *J. Clean. Prod.* 156, 624–634. doi:10.1016/j.jclepro.2017.04.091
- Perez-Garcia, J., Lippke, B., Cornick, J., and Manriquez, C. (2005). An Assessment of Carbon Pools, Storage, and wood Products Market Substitution Using Life-Cycle Analysis Results. *Wood Fiber Sci.* 37, 140–148.
- Pour, N., Webley, P. A., and Cook, P. J. (2018). Opportunities for Application of BECCS in the Australian Power Sector. *Appl. Energy* 224, 615–635. doi:10.1016/j.apenergy.2018.04.117
- Pradhan, P., Arora, A., and Mahajani, S. M. (2018). Pilot Scale Evaluation of Fuel Pellets Production from Garden Waste Biomass. *Energy. Sustain. Dev.* 43, 1–14. doi:10.1016/j.esd.2017.11.005
- Prokkola, H. E., Kuokkanen, M., Kuokkanen, T., and Lassi, U. (2014). Chemical Study of wood Chip Drying: Biodegradation of Organic Pollutants in Condensate Waters from the Drying Process. *BioResources* 9, 3761–3778. doi:10.15376/biores.9.3.3761-3778
- Purohit, P., and Chaturvedi, V. (2018). Biomass Pellets for Power Generation in India: a Techno-Economic Evaluation. *Environ. Sci. Pollut. Res.* 25, 29614–29632. doi:10.1007/s11356-018-2960-8
- Puy, N., Murillo, R., Navarro, M. V., López, J. M., Rieradevall, J., Fowler, G., et al. (2011). Valorisation of Forestry Waste by Pyrolysis in an Auger Reactor. *Waste Manage.* 31, 1339–1349. doi:10.1016/j.wasman.2011.01.020
- Raunika, R., Buongiorno, J., Turner, J. A., and Zhu, S. (2010). Global Outlook for wood and Forests with the Bioenergy Demand Implied by Scenarios of the Intergovernmental Panel on Climate Change. *For. Pol. Econ.* 12, 48–56. doi:10.1016/j.forpol.2009.09.013
- Royo, J., Sebastián, F., García-Galindo, D., Gómez, M., and Díaz, M. (2012). Large-scale Analysis of GHG (Greenhouse Gas) Reduction by Means of Biomass Co-firing at Country-Scale: Application to the Spanish Case. *Energy* 48, 255–267. doi:10.1016/j.energy.2012.06.046
- Sandro, N., Agis, P., Gojmir, R., Vlasta, Z., and Müslüm, A. (2019). Using Pellet Fuels for Residential Heating: A Field Study on its Efficiency and the Users' Satisfaction. *Energy and Buildings* 184, 193–204. doi:10.1016/j.enbuild.2018.12.007
- Sarkar, S., and Kumar, A. (2010). Large-scale Biohydrogen Production from Bio-Oil. *Bioresour. Technol.* 101, 7350–7361. doi:10.1016/j.biortech.2010.04.038
- Sarkar, S., and Kumar, A. (2009). Techno-Economic Assessment of Biohydrogen Production from Forest Biomass in Western Canada. *Trans. ASABE* 52, 519–530.
- Sasujit, K., Dussadee, N., Homdoun, N., Ramaraj, R., and Kiatsiriroat, T. (2017). Waste-to-Energy: Producer Gas Production from Fuel Briquette of Energy Crop in Thailand. *Int. Energy J.* 17, 37–46.
- Scarlat, N., Blujdea, V., and Dallemand, J.-F. (2011). Assessment of the Availability of Agricultural and forest Residues for Bioenergy Production in Romania. *Biomass Bioenergy* 35, 1995–2005. doi:10.1016/j.biombioe.2011.01.057
- Schulzke, T. (2019). Biomass Gasification: Conversion of forest Residues into Heat, Electricity and Base Chemicals. *Chem. Pap.* 78, 1833–1852. doi:10.1007/s11696-019-00801-1
- Searle, S. Y., and Malins, C. J. (2016). Waste and Residue Availability for Advanced Biofuel Production in EU Member States. *Biomass Bioenergy* 89, 2–10. doi:10.1016/j.biombioe.2016.01.008
- Sharma, B., Larroche, C., and Dussap, C.-G. (2020). Comprehensive Assessment of 2G Bioethanol Production. *Bioresour. Technol.* 313, 123630. doi:10.1016/j.biortech.2020.123630
- Shih, H.-Y., and Hsu, J.-R. (2011). A Computational Study of Combustion and Extinction of Opposed-Jet Syngas Diffusion Flames. *Int. J. Hydrogen Energy* 36, 15868–15879. doi:10.1016/j.ijhydene.2011.09.037
- Sikkema, R., Steiner, M., Junginger, M., Hiegl, W., Hansen, M. T., and Faaij, A. (2011). The European wood Pellet Markets: Current Status and Prospects for 2020. *Biofuels, Bioprod. Bioref.* 5, 250–278. doi:10.1002/bbb.277
- Solar, J., Caballero, B., De Marco, I., López-Urionabarrenechea, A., and Gastelu, N. (2018). Optimization of Charcoal Production Process from Woody Biomass Waste: Effect of Ni-Containing Catalysts on Pyrolysis Vapors. *Catalysts* 8, 191. doi:10.3390/catal8050191
- Soltanian, S., Aghbashlo, M., Almasi, F., Hosseinzadeh-Bandbafha, H., Nizami, A.-S., Ok, Y. S., et al. (2020). A Critical Review of the Effects of Pretreatment Methods on the Exergetic Aspects of Lignocellulosic Biofuels. *Energy. Convers. Manage.* 212, 112792. doi:10.1016/j.enconman.2020.112792
- Stefanidis, S. D., Heracleous, E., Patiaka, D. T., Kalogiannis, K. G., Michailof, C. M., and Lappas, A. A. (2015). Optimization of Bio-oil Yields by Demineralization of Low Quality Biomass. *Biomass Bioenergy* 83, 105–115.
- Sunde, K., Brekke, A., and Solberg, B. (2011). Environmental Impacts and Costs of Woody Biomass-To-Liquid (BTL) Production and Use - A Review. *For. Pol. Econ.* 13, 591–602. doi:10.1016/j.forpol.2011.05.008
- Tabatabaei, M., Aghbashlo, M., Valijanian, E., Kazemi Shariat Panahi, H., Nizami, A.-S., Ghanavati, H., et al. (2020a). A Comprehensive Review on Recent Biological Innovations to Improve Biogas Production, Part 1: Upstream Strategies. *Renew. Energy* 146, 1204–1220. doi:10.1016/j.renene.2019.07.037
- Tabatabaei, M., Aghbashlo, M., Valijanian, E., Kazemi Shariat Panahi, H., Nizami, A.-S., Ghanavati, H., et al. (2020b). A Comprehensive Review on Recent Biological Innovations to Improve Biogas Production, Part 2: Mainstream and Downstream Strategies. *Renew. Energy* 146, 1392–1407. doi:10.1016/j.renene.2019.07.047
- Taherzadeh, M., and Karimi, K. (2008). Pretreatment of Lignocellulosic Wastes to Improve Ethanol and Biogas Production: a Review. *Ijms* 9, 1621–1651. doi:10.3390/ijms9091621

- Tamura, M., Watanabe, S., Kotake, N., and Hasegawa, M. (2014). Grinding and Combustion Characteristics of Woody Biomass for Co-firing with Coal in Pulverised Coal Boilers. *Fuel* 134, 544–553. doi:10.1016/j.fuel.2014.05.083
- Tan, Z., Chen, K., and Liu, P. (2015). Possibilities and Challenges of China's Forestry Biomass Resource Utilization. *Renew. Sustain. Energ. Rev.* 41, 368–378. doi:10.1016/j.rser.2014.08.059
- Tsalidis, G.-A., Joshi, Y., Korevaar, G., and de Jong, W. (2014). Life Cycle Assessment of Direct Co-firing of Torrefied And/or Pelletised Woody Biomass with Coal in The Netherlands. *J. Clean. Prod.* 81, 168–177. doi:10.1016/j.jclepro.2014.06.049
- Urban, L., Masa, V., Pavlas, M., and Stehlik, P. (2010). Novel Type of Technology for Biomass Utilization. *Forestry* 2020, 2030.
- Valdés, C. F., Marrugo, G., Chejne, F., Cogollo, K., and Vallejos, D. (2018). Pelletization of Agroindustrial Biomasses from the Tropics as an Energy Resource: Implications of Pellet Quality. *Energy Fuels* 32, 11489–11501. doi:10.1021/acs.energyfuels.8b01673
- Vandenbroek, R., Faaij, A., and van Wijk, A. (1996). Biomass Combustion for Power Generation. *Biomass Bioenergy* 11, 271–281. doi:10.1016/0961-9534(96)00033-5
- van Schalkwyk, D. L., Mandegari, M., Farzad, S., and Görgens, J. F. (2020). Techno-economic and Environmental Analysis of Bio-Oil Production from forest Residues via Non-catalytic and Catalytic Pyrolysis Processes. *Energ. Convers. Manage.* 213, 112815. doi:10.1016/j.enconman.2020.112815
- Vassilev, S. V., Baxter, D., Andersen, L. K., and Vassileva, C. G. (2010). An Overview of the Chemical Composition of Biomass. *Fuel* 89, 913–933. doi:10.1016/j.fuel.2009.10.022
- Wang, H., Zhang, S., Bi, X., and Clift, R. (2020). Greenhouse Gas Emission Reduction Potential and Cost of Bioenergy in British Columbia, Canada. *Energy Policy* 138, 111285. doi:10.1016/j.enpol.2020.111285
- Welfle, A., Gilbert, P., and Thornley, P. (2014). Securing a Bioenergy Future without Imports. *Energy Policy* 68, 1–14. doi:10.1016/j.enpol.2013.11.079
- Yamamoto, M., Niskanen, T., Iakovlev, M., Ojamo, H., and van Heiningen, A. (2014). The Effect of Bark on Sulfur Dioxide-Ethanol-Water Fractionation and Enzymatic Hydrolysis of forest Biomass. *Bioresour. Technol.* 167, 390–397. doi:10.1016/j.biortech.2014.06.019
- Yek, P. N. Y., Peng, W., Wong, C. C., Liew, R. K., Ho, Y. L., Wan Mahari, W. A., et al. (2020). Engineered Biochar via Microwave CO₂ and Steam Pyrolysis to Treat Carcinogenic Congo Red Dye. *J. Hazard. Mater.* 395, 122636. doi:10.1016/j.jhazmat.2020.122636
- Yin, C., Rosendahl, L. A., and Kær, S. K. (2008). Grate-firing of Biomass for Heat and Power Production. *Prog. Energ. Combustion Sci.* 34, 725–754. doi:10.1016/j.peccs.2008.05.002
- Yuan, R., Yu, S., and Shen, Y. (2019). Pyrolysis and Combustion Kinetics of Lignocellulosic Biomass Pellets with Calcium-Rich Wastes from Agro-Forestry Residues. *Waste Manage.* 87, 86–96. doi:10.1016/j.wasman.2019.02.009
- Zabed, H., Sahu, J. N., Boyce, A. N., and Faruq, G. (2016). Fuel Ethanol Production from Lignocellulosic Biomass: an Overview on Feedstocks and Technological Approaches. *Renew. Sustain. Energ. Rev.* 66, 751–774. doi:10.1016/j.rser.2016.08.038
- Zamora, D. S., Apostol, K. G., and Wyatt, G. J. (2014). Biomass Production and Potential Ethanol Yields of Shrub Willow Hybrids and Native Willow Accessions after a Single 3-year Harvest Cycle on Marginal Lands in central Minnesota, USA. *Agroforest Syst.* 88, 593–606. doi:10.1007/s10457-014-9693-6
- Zhao, J., Xu, Y., Wang, W., Griffin, J., Roozeboom, K., and Wang, D. (2020). Bioconversion of Industrial Hemp Biomass for Bioethanol Production: A Review. *Fuel* 281, 118725. doi:10.1016/j.fuel.2020.118725
- Zheng, T., Jiang, J., and Yao, J. (2020). Surfactant-promoted Hydrolysis of Lignocellulose for Ethanol Production. *Fuel Process. Technol.*, 106660. doi:10.1016/j.fuproc.2020.106660
- Zhu, J. Y., Chandra, M. S., Gu, F., Gleisner, R., Reiner, R., Sessions, J., et al. (2015). Using Sulfite Chemistry for Robust Bioconversion of Douglas-fir forest Residue to Bioethanol at High Titer and Lignosulfonate: a Pilot-Scale Evaluation. *Bioresour. Technol.* 179, 390–397. doi:10.1016/j.biortech.2014.12.052
- Zomer, R. J., Trabucco, A., Bossio, D. A., and Verchot, L. V. (2008). Climate Change Mitigation: A Spatial Analysis of Global Land Suitability for Clean Development Mechanism Afforestation and Reforestation. *Agric. Ecosyst. Environ.* 126, 67–80. doi:10.1016/j.agee.2008.01.014

Conflict of Interest: The author SSL had previously collaborated with the reviewer CTC.

The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

Copyright © 2021 Yu, Wang, Van Le, Yang, Hosseinzadeh-Bandbafha, Yang, Sonne, Tabatabaei, Lam and Peng. This is an open-access article distributed under the terms of the Creative Commons Attribution License (CC BY). The use, distribution or reproduction in other forums is permitted, provided the original author(s) and the copyright owner(s) are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.