



Strength-Endurance: Interaction Between Force-Velocity Condition and Power Output

Jean Romain Rivière^{1*}, Nicolas Peyrot², Matthew R. Cross¹, Laurent A. Messonnier¹ and Pierre Samozino¹

¹ Univ Savoie Mont Blanc, Laboratoire Interuniversitaire de Biologie de la Motricité, EA 7424, Chambéry, France, ² Le Mans Université, Movement-Interactions-Performance, MIP, EA 4334, Le Mans, France

Context: Strength-endurance mainly depends on the power output, which is often expressed relative to the individual's maximal power capability (P_{max}). However, an individual can develop the same power, but in different combinations of force and velocity (force-velocity condition). Also, at matched power output, changing the force-velocity condition results in a change of the velocity-specific relative power ($P_{max}v$), associated with a change in the power reserve. So far, the effect of these changing conditions on strength-endurance remains unclear.

OPEN ACCESS

Edited by:

Anthony John Blazevich, Edith Cowan University, Australia

Reviewed by:

Harry George Banyard, Swinburne University of Technology, Australia Alejandro Pérez-Castilla, University of Granada, Spain

> *Correspondence: Jean Romain Rivière jean.r.riviere@gmail.com

Specialty section:

This article was submitted to Exercise Physiology, a section of the journal Frontiers in Physiology

Received: 26 June 2020 Accepted: 04 September 2020 Published: 09 October 2020

Citation:

Rivière JR, Peyrot N, Cross MR, Messonnier LA and Samozino P (2020) Strength-Endurance: Interaction Between Force-Velocity Condition and Power Output. Front. Physiol. 11:576725. doi: 10.3389/fphys.2020.576725 **Purpose:** We aimed to test the effects of force-velocity condition and power output on strength-endurance.

Methods: Fourteen sportsmen performed (i) force- and power-velocity relationships evaluation in squat jumps and (ii) strength-endurance evaluations during repeated squat jump tests in 10 different force-velocity-power conditions, individualized based on the force- and power-velocity relationships. Each condition was characterized by different (i) relative power ($\%P_{max}$), (ii) velocity-specific relative power ($\%P_{max}v$), and (iii) ratio between force and velocity (R_{Fv}). Strength-endurance was assessed by the maximum repetitions (SJ_{Rep}), and the cumulated mechanical work (W_{tot}) performed until exhaustion during repeated squat jump tests. Intra and inter-day reliability of SJ_{Rep} were tested in one of the 10 conditions. The effects of $\%P_{max}$, $\%P_{max}v$, and R_{Fv} on SJ_{Rep} and W_{tot} were tested via stepwise multiple linear regressions and two-way ANOVAs.

Results: SJ_{Rep} exhibited almost perfect intra- and inter-day reliability (ICC=0.94 and 0.92, respectively). SJ_{Rep} and W_{tot} were influenced by $\%P_{\text{max}}v$ and R_{Fv} (R^2 =0.975 and 0.971; RSME=0.243 and 0.234, respectively; both p < 0.001), with the effect of R_{Fv} increasing with decreasing $\%P_{\text{max}}v$ (interaction effect, p = 0.03). $\%P_{\text{max}}$ was not considered as a significant predictor of strength-endurance by the multiple regressions analysis. SJ_{Rep} and W_{tot} were higher at lower $\%P_{\text{max}}v$ and in low force-high velocity conditions (i.e., lower R_{Fv}).

Conclusion: Strength-endurance was almost fully dependent on the position of the exercise conditions relative to the individual force-velocity and power-velocity

1

relationships (characterized by $%P_{max}v$ and R_{Fv}). Thus, the standardization of the forcevelocity condition and the velocity-specific relative power should not be overlooked for strength-endurance testing and training, but also when setting fatiguing protocols.

Keywords: force-velocity relationship, power-velocity relationship, test to exhaustion, repeated jump test, power reserve, force-velocity ratio, power-velocity-endurance profile

INTRODUCTION

Repetitive near-maximal- or maximal-intensity efforts, such as sprinting, rowing, jumping, or stair climbing, are frequent in daily life and sporting activity. The key to successful performance during repeated movements relies on the production of mechanical power and its maintenance over a series of repetitions until task completion.

Power production capabilities depend on movement velocity and are well-represented by the parabolic power-velocity (Pv) relationship during multi-joint movements (Bobbert, 2012; Samozino et al., 2012; Jaric, 2015). The apex of the P-v relationships corresponds to the maximal power attained at optimal velocity (P_{max}), which is commonly accepted as a macroscopic measure of dynamic strength capabilities (Jaric, 2015; Alcazar et al., 2017). The ability to maintain power over a series of movements (i.e., strength-endurance) depends primarily on the output magnitude and is well-illustrated by the power-time relationship. Two distinct power-time relationships have been reported to characterize strength-endurance: (i) the inverse hyperbolic relationship between the absolute or relative power output and the duration during which this given power can be maintained, which can be obtained from 3 to 5 tests to exhaustion (Monod and Scherrer, 1965; Burnley and Jones, 2016), and (ii) the decrease in instantaneous power output over time during a single all-out exercise, which is instead associated with fatigability indices, such as the rate of power output loss over 30-s all-out cycling (Bar-Or, 1987). However, the same absolute or relative-to- P_{max} (% P_{max}) power output can be developed in high force-low velocity conditions or in low force-high velocity conditions, and these different force-velocity (F-v) conditions can be interpreted as distinct ratios between the force output and the movement velocity $(R_{\rm Fv})$.

The effect of $R_{\rm Fv}$ on strength-endurance has been studied indirectly by investigating the effect of movement velocity using cyclic (e.g., cycling) and acyclic movements (e.g., knee extension; Elert and Gerdle, 1989; Barker et al., 2006). Due to the specificity of cyclic movements, velocity is indirectly controlled by adjusting movement frequency (e.g., the pedaling cadence) or using a specific set-ups (Dorel et al., 2003; Tomas et al., 2010). During allout exercises, higher fatigability has been systematically observed at higher compared to lower movement frequencies in cyclic movements (i.e., cycling; e.g., Sargeant et al., 1981; Beelen and Sargeant, 1991a). However, there is little consensus in acyclic movements (i.e., knee extension and shoulder flexion) since some studies report higher fatigability at higher movement velocities (e.g., Mathiassen, 1989; Morel et al., 2015) while others report opposite results (Elert and Gerdle, 1989; Dalton et al., 2012). Moreover, R_{Fv} and $%P_{max}$ conditions were not fixed at each repetition over the tests due to the decrease in power output throughout all-out exercises. Consequently, it is challenging to evaluate the effects of R_{Fv} and %P_{max} on strength-endurance, as well as the interactions between both mechanical conditions by the mean of all-out exercises. During tests to exhaustion performed at constant power output, only cyclic movements (i.e., cycling and paddling) were used to study the effect of $R_{\rm Fy}$ on strength-endurance. Similarly, there is a lack of consensus since some studies reported lower strength-endurance at higher movement frequencies (Carnevale and Gaesser, 1991; Barker et al., 2006) and others, lower strength-endurance at lower movement frequencies (Leveque et al., 2002; Bessot et al., 2006). Moreover, the sole effect of R_{Fv} cannot be examined when using cyclic movements due to the concomitant influence of both movement frequency and velocity on strength-endurance. Indeed, movement frequency alone impacts strength-endurance by changing (i) rest between repetitions and (ii) contraction number during a test of fixed duration (Enoka and Stuart, 1992; Broxterman et al., 2014). A lower time-to-exhaustion observed at higher movement frequencies can thus be due to shorter rest time between contractions and/or more contractions and/or higher contraction velocities. Overall, investigating the effect $R_{\rm Fy}$ on strength-endurance requires (i) the use of an acyclic movement, allowing the dissociation with the effect of movement frequency, and (ii) the use of time-to exhaustion at constant power to control force-velocity and power output conditions throughout the test.

In parallel to $R_{\rm Fv}$, strength-endurance can also be influenced by the power reserve. Indeed, due to the parabolic shape of the Pv relationship, a change in $R_{\rm Fv}$ at a matched $\% P_{\rm max}$ is associated with a change in the power reserve. This reserve corresponds to the difference between the maximal power capability at a specific velocity and the power output at the same specific velocity (Sargeant, 1994, 2007; Zoladz et al., 2000). This reserve can also be interpreted as a velocity-specific relative power ($%P_{max}v$): the lower $\%P_{\max}v$, the larger the power reserve. When considering the same %P_{max}, low force-high velocity conditions (often close to the optimal velocity) are associated with larger power reserve and lower $\%P_{\max}v$, and might improve strength-endurance (Sargeant, 1994, 2007; Zoladz et al., 2000). Nevertheless, due to the concomitant change of $R_{\rm Fv}$ and $\% P_{\rm max} v$ at matched $\% P_{\rm max}$, it remains unclear whether the influence of R_{Fv} on strengthendurance is independent of $\[max] P_{\max} v$. Also, as matched $\[max] P_{\max} v$ can lead to different $%P_{\text{max}}$, the question of which of the two indices better represents exercise intensity remains unanswered.

Clarifying the effect of P_{max} , P_{max} , and R_{Fv} on strengthendurance could be of great interest for scientific and training purposes since typical strength-endurance evaluations have been standardized across individuals based on (i) the same relative load (e.g., percentage of the one-repetition maximum; Mayhew et al., 1992), (ii) the same movement velocity across individuals (Câmara et al., 2012) or (iii) the same resistive force per bodyweight during all-out cycling exercises (Bar-Or, 1987). Thus, provided R_{Fv} affects performance, inter-individual differences in strength-endurance observed with these commonly used methods could be mainly due to different mechanical conditions relative to individual capabilities (i.e., $\% P_{max}$, $\% P_{max}v$, and/or R_{Fv}) rather than different physical abilities. These methods could represent both an inaccurate and non-specific means of assessing strength-endurance, and lead to practically ineffective testing and training regimes.

The aim of the present study was to test the effects of forcevelocity condition (i.e., $R_{\rm Fv}$) and power output (i.e., $\% P_{\rm max}$ and $\% P_{\rm max} \nu$) on strength-endurance using an acyclic movement. We hypothesized that decreasing velocity-specific relative power ($\% P_{\rm max} \nu$) increases strength-endurance *via* increasing power reserve, even if it led to no change or an increase in $\% P_{\rm max}$. We theorized that $R_{\rm Fv}$ influences strength-endurance independently from $\% P_{\rm max} \nu$, due to the likely different etiology of fatigue between high force-low velocity and low force-high velocity conditions (Enoka and Stuart, 1992; Morel et al., 2015, 2019).

MATERIALS AND METHODS

Participants

Fourteen healthy participants (12 males and 2 females, age = 20 ± 2 years, mass = 73 ± 7 kg and height = 1.79 ± 0.09 m) gave their written informed consent to participate in this study, with all procedures in agreement with the declaration of Helsinki and the ethical standards of a local committee. All were involved in regular physical activity (14 ± 7 h of training per week) and were accustomed to strength-based resistance training (i.e., habitual use of submaximal to maximal loads). All participants were free of musculoskeletal pain or injury during the study.

Design

The main limitations of previous works were addressed in this study by using jumping exercises due to (i) the possibility to dissociate rest between repetitions from movement velocity, (ii) the acute and reliable quantification of the mean force, velocity, and power output by lower limbs, and (iii) its similarity to typical iso-inertial movements observed in sport and testing batteries.

To test the effects of $\%P_{\max}v$, $\%P_{\max}$, and R_{Fv} on strengthendurance, repeated squat jumps (RSJ) tests to exhaustion were performed in various force-velocity-power (*F-v-P*) conditions. Overall, 10 *F-v-P* conditions were determined relative to individual *P-v* relationship (detailed in the following sections), which meant conditions were graphically positioned on or under the *P-v* curve (gray points, **Figure 1**). This positioning of the *F-v-P* conditions implies each condition has similar coordinates relative to individual maximal capabilities (i.e., the *P-v* relationship), but various individual absolute force, velocity and power values. Thus, each *F-v-P* conditions was characterized by different power output (*P*₁ to *P*₅) and velocity (*v*₁ to *v*₆),



FIGURE 1 Typical individual power-velocity relationship representing 100 (black curve) and $85\%P_{max}v$ (gray curve), associated with single maximal squat jumps in different loading conditions (white points) and the 10 *F-v-P* conditions (gray points). Each *F-v-P* conditions is defined by specific power and velocity coordinates. The dashed gray curve represents the different power-velocity conditions for jumps without load, from sub-maximal to maximal jump height. The crosshatched area under the gray and the black curve represents all power-velocity conditions that require assistance (i.e., total load lower than body mass), and thus were not measured.

expressed relative to the individual P-v relationship (Figure 1). In addition, the positioning of F-v-P conditions follows the constraint imposed by dynamics principles during a vertical jump with and without additional load (represented by the white area under the P-v curve and the dashed gray line, respectively, Figure 1). The remaining crosshatched area represents F-v-P conditions requiring a simulated reduction in body weight with assistance.

The 10 *F-v-P* conditions were selected to represent: (i) 3 velocity conditions at two $%P_{max}$ (corresponding to P_3v_3 , P_3v_4 , and P_3v_6 at 85% P_{max} and to P_2v_2 , P_2v_3 , and P_2v_5 at $\sim 73\%P_{max}$), (ii) 3 velocity conditions at two $%P_{max}v$ (corresponding to P_1v_1 , P_2v_3 , and P_3v_6 at 85% $P_{max}v$ and P_2v_2 , P_3v_3 , and P_4v_6 at 100% $P_{max}v$) and (iii) 3 power conditions at two velocities (corresponding to P_5v_6 , P_4v_6 , and P_3v_6 at v_6 and to P_3v_3 , P_2v_3 , and P_1v_3 at v_3). Note that all *F-v-P* conditions were determined only using power and velocity values to graphically position them relative to power capability as a common reference (i.e., *P-v* relationship), but changes in velocity across all different power conditions correspond also to changes in R_{Fv} .

Protocol

This study comprised six sessions, separated by more than 48h of rest (Figure 2). The first session familiarized participants



in performing (i) single maximal effort squat jump (SJ) with and without load (range of loads detailed in Section "Force- and Power-Velocity Relationships Assessment") and (ii) unloaded RSJs test until exhaustion (see section "Measurements and Data Analysis" for the exact definition of exhaustion). In the second session, individual F-v and P-v relationships of the lower limbs were evaluated from SJ with and without additional loads, then RSJ test was performed in one specific F-v-P conditions (P_3v_4) for inter-day reliability analysis. From the third to the sixth session, each participant performed 12 RSJ tests randomly organized into 3 per session and separated by 30 min of passive rest (e.g., Karsten et al., 2016; Triska et al., 2017), which corresponded to: 1 RSJ test in each of the 10 F-v-P conditions, 1 RSJ test repeated one more time to assess intra-day reliability in the specific F-v-P conditions (P_3v_4) and 1 RSJ test was not included in the data analysis of the present study (black vertical RSJ bar, Figure 2), because this test is dedicated to answer another aim not addressed here.

The six sessions began with body mass measurements and a standardized warm-up consisting of 5 min of self-paced treadmill running followed by \sim 15 min of dynamic lower-limb movements (including unloaded squats with maximal intention and sub-maximal and maximal SJs in unloaded and loaded conditions) and concluding with 5 min of non-fatiguing personally selected exercises.

Familiarization Sessions

During the first session, the familiarization occurred in two distinct sets. The first set aimed to familiarize participants with the *F-v* and *P-v* relationships evaluation procedures. This first set included the same procedures as during the session 2, which are described in the next section, "Force- and Power-Velocity Relationships Assessment." The second set aimed to familiarize participants with the RSJ test. This second set comprised (i) three trials of unloaded RSJ, targeting ~50% of maximal jump height, separated each by 5 min of rest and ended when 10 successive repetitions were successfully performed at the target and, after 30 min of passive rest, (ii) two unloaded RSJ tests, aiming for maintaining the effort of maximal jump height until exhaustion, interspersed by 30 min of passive rest. During this familiarization session, individual starting position for RSJ tests and *F-v* and *P-v* relationships assessment was recorded

and was standardized throughout the study. The preferential starting position was chosen by the participant, which has been shown as the method with which force, velocity, and power output are maximized and most reliable in squat jump (Janicijevic D. et al., 2019; Janicijevic D. N. et al., 2019). Using a barbell or a wooden dowel held across the shoulders, the starting position was matched with lateral adjustable supports (~1 cm resolution), preventing participants from going beyond the starting position during the downward movement of SJ (**Figure 3**). Individual push-off distance (h_{po}) was determined as the difference between the length of the lower limbs extended with maximal foot plantarflexion (iliac crest-toe distance) and the vertical distance between iliac crest and ground in the starting position.

Force- and Power-Velocity Relationships Assessment

The determination of individual F- ν and P- ν relationships included 5 SJs with loading conditions ranging from 0 to 100% of body weight, with each condition performed twice. For each trial, participants stood stationary holding a barbell on their shoulders for additional-load conditions or a wooden dowel (~400 g) for the unloaded condition (i.e., 0% of body weight). They lowered the bar to reach their individual starting position



and after maintaining this position for 2 to 3 s, they were asked to jump maximally without countermovement. They were also prompted to touch down in the same leg position as they took off: extended leg with foot plantar flexion. If these requirements were not met, the trial was discarded, and then repeated. The trial with the greatest jump height across all trials was used to determine individual F-v and P-v relationships (Samozino et al., 2008, 2014). When the force exerted against a certain load led to the coefficient of determination of the F-v relationship to be lower than 0.96, a third repetition was performed with that specific load to infirm or confirm the trial.

Repeated Jump Test

For each RSJ test, the practical setting of a given F- ν -P condition consisted of modulating the additional load and the jump height based on fundamental laws of dynamics and following the equations proposed and validated by Samozino et al. (2008). Briefly, during the push-off phase of SJs, the mean force (F, Eq. 1), velocity (ν , Eq. 2), and power (P, Eq. 3) developed by the lower limbs can be expressed as:

$$F = (m_{\text{body}} + m_{\text{bar}})g(\frac{h}{h_{\text{po}}} + 1) \quad (Eq. 1)$$
$$v = \sqrt{\frac{gh}{2}} \qquad (Eq. 2)$$
$$P = (m_{\text{body}} + m_{\text{bar}})g(\frac{h}{h_{\text{po}}} + 1)\sqrt{\frac{gh}{2}} \quad (Eq. 3)$$

where m_{body} is the body mass, m_{bar} the mass of the bar (including the mass of the bar [10 kg] and the additional mass), *g* the gravitational acceleration (9.81 m.s⁻²), and *h* the jump height. From Eqs 1 and 2, the jump height (Eq. 4) and the additional mass (Eq. 5) can be computed as a function of the targeted *F-v-P* conditions:

$$h = \frac{2\nu^2}{g} \tag{Eq. 4}$$

$$m_{\text{bar}} = \frac{\frac{P}{v}}{g(\frac{h}{h_{\text{po}}}) + 1} - m_{\text{body}} \qquad (Eq. 5)$$

Consequently, participants were instructed to reach a targeted jump height under a specific loading condition, which allowed them to perform an RSJ test in targeted F-v-P conditions. The jump height was self-controlled and aided by continuous visual feedback of the jump height that was displayed, repetition by repetition, to the screen in front of the participant (**Figure 3**). Where the required additional mass was lower than the mass of the bar, participants wore a weighted vest with the appropriated added load (0.5 kg resolution) and the wooden dowel. The jumping frequency was adjusted at each RSJ test, considering 2.5 s rest time between two successive SJs. The jumping frequency was monitored using two audible beeps to signal (i) the initiation of the downward movement to reach the starting position and (ii) the initiation of the jump. Participants were verbally encouraged to maintain the targeted jump height as long as possible (i.e., until exhaustion). Once jump height dropped below the target, participants were provided with strong encouragements to continue with maximal intent (i.e., aiming for maximal height). All procedures were monitored by the experimenters via their own screen, hidden from the participants during their trials.

Measurements and Data Analysis

For SJs performed during RSJ tests and F- ν and P- ν relationships assessment, force, velocity, and power developed during the push-off phase were computed using Eqs 1–3. The jump height was determined from fundamental laws of dynamics and aerial time (Asmussen and Bonde-Petersen, 1974), the latter being obtained using an infrared timing system (OptoJumpNext, Microgate, Bolzano, Italy). For each participant, the *F*- ν and *P*- ν relationships were determined from *F*, ν , and *P* values obtained from the 5 loading SJ conditions and were used to extrapolate *F*₀ and ν_0 , the y and × intercept of the *F*- ν relationship, respectively. Then, P_{max} was computed as (Samozino et al., 2012):

$$P_{max} = \frac{F_0 v_0}{4} \tag{Eq. 6}$$

For each of the 10 RSJ conditions, $R_{\rm Fv}$ was computed as the ratio between the force developed (expressed relative to F_0) and the velocity (expressed relative to v_0). Exhaustion was defined as the inability to perform three consecutive jumps above 95% of the targeted jump height. Strength-endurance was quantified by (i) the maximum repetitions ($SJ_{\rm Rep}$) and (ii) the cumulated mechanical work output ($W_{\rm tot}$) associated to $SJ_{\rm Rep}$. $SJ_{\rm Rep}$ corresponded to all repetitions preceding exhaustion, excluding the three jumps below the limit of 95% of the targeted performance and $W_{\rm tot}$ was computed as the sum of the mechanical work of all repetitions of $SJ_{\rm Rep}$.

Statistical Analysis

All data are presented as mean \pm standard deviation (SD). Intra-set RSJ height variability around the targeted jump height value was assessed using a coefficient of variation. Also, absolute intra- and inter-day reliability of SJ_{Rep} in P_3v_4 condition were assessed with the standard error of measurement (SEM; Hopkins et al., 2001) expressed in raw units and standardized to inter-individual SD. Relative intraand inter-day reliability of SJ_{Rep} in P_3v_4 condition were assessed with intra-class correlation coefficient (ICC), which was interpreted as almost perfect (0.81 to 1.00), substantial (0.61 to 0.80), moderate (0.41 to 0.60), fair (0.21 to 0.40), slight (0.01 to 0.20), or poor (<0.01; Landis and Koch, 1977). The difference between the two trials was tested with the paired sample *t*-test.

The respective effects of $%P_{\text{max}}$, $%P_{\text{max}}v$, and R_{Fv} on both SJ_{rep} and W_{tot} were examined using two separate stepwise multiple linear regressions performed from averaged data of the 10 *F-v-P* conditions of RSJ tests (n = 10), with $%P_{\text{max}}$, $%P_{\text{max}}v$, and R_{Fv} as independent variables and SJ_{rep} or W_{tot} (log-transformed to support linearity of relationships, Monod and

Scherrer, 1965; Jones and Vanhatalo, 2017) as the dependent variable. To test the main effects of $%P_{\text{max}}$, $%P_{\text{max}}v$ and R_{Fv} on both SJ_{rep} and W_{tot} , as well as their interaction, 2 twoway ANOVAs with repeated measures were performed on SJ_{rep} and W_{tot} , separately: (i) effects of R_{Fv} (low, medium and high levels) and % P_{max} (~73% P_{max} and ~85% P_{max}) and (ii) effects of $R_{\rm Fv}$ (low, medium, and high levels) and $\% P_{\rm max} v$ $(85\%P_{\text{max}}\nu \text{ and } 100\%P_{\text{max}}\nu)$. Each ANOVA was performed after checking for distribution normality and equality of variance with Shapiro-Wilk's and Mauchly's test, respectively. In the case of non-normality and violation of the assumption of sphericity, the non-linear logarithm transformation and the Greenhouse-Geisser's correction were applied, respectively (Sainani, 2012). Holm's post hoc test was used to highlight significant differences between conditions, as well as simple main effects to test the effect of the first main factor at each level of the second factor, and vice-versa. For all statistical analyses, an alpha value of 0.05 was accepted as the level of significance.

RESULTS

All individual *F*-*v* relationships fitted by linear regressions showed very high quality ($R^2 = 0.98$ to 1; p < 0.001), and were associated to F_0 of 2202 ± 317 N (30.1 ± 3.5 N.kg⁻¹), v_0 of 2.79 ± 0.43 m.s⁻¹, P_{max} of 1542 ± 329 W (21.0 ± 4.0 W.kg⁻¹) and h_{po} of 0.45 ± 0.06 m. The SEM, ICC, and *t*-test's *p*-values between the trials performed in the P_3v_4 condition to assess intra-day and inter-day reliability are presented in **Table 1**. RSJ additional load, targeted jump height, intraset coefficient of variation of jump height, and jumping frequency associated with the 10 *F-v-P* conditions are presented in **Table 2**. SJ_{Rep} , R_{Fv} , W_{tot} , as well as the targeted and achieved absolute and relative force, velocity, and power values associated with the 10 *F-v-P* conditions are presented in **Table 3**.

The stepwise multiple regression analysis with SJ_{rep} as the dependent variable showed that $\%P_{\max}\nu$ (88.4% of the variance explained, beta-weight of -0.812) and $R_{\rm Fv}$ (9.1% of the variance explained, standardized beta-weight of -0.327) accounted for a significant amount of SJ_{rep} variability (p < 0.001; F = 134.187). The regression model obtained was $\ln(SJ_{\rm Rep}) = 17.042 - 0.144(\%P_{\max}\nu) - 0.649(R_{\rm Fv})$, which indicated a very high goodness of fit ($R^2 = 0.975$, p < 0.001), with low residuals (RSME = 0.243).

The stepwise multiple regression analysis with W_{tot} as the dependent variable showed that $%P_{\text{max}}v$ (89.2% of the variance explained, beta-weight of -0.825) and R_{Fv} (7.9% of the variance explained, standardized beta-weight of -0.305) accounted for a significant amount of W_{tot} variability (p < 0.001; F = 116.866). The regression model obtained was $\ln(W_{\text{tot}}) = 22.140 - 0.132(%P_{\text{max}}v) - 0.545(R_{\text{Fv}})$, which indicated a very high goodness of fit ($R^2 = 0.971$, p < 0.001), with low residuals (RSME = 0.234).

Effect of R_{Fv} and $%P_{max}$ on SJ_{rep} and W_{tot}

The two-way ANOVA with repeated measures testing the effect of $\%P_{\text{max}}$ and R_{Fv} on SJ_{rep} showed a main effect of R_{Fv} (p < 0.001) and $R_{\text{Fv}} \times \%P_{\text{max}}$ interaction (p < 0.001), but no main effect of $\%P_{\text{max}}$ (p = 0.129; **Figure 4A**). Post hoc comparisons revealed significant differences (p < 0.001) for all comparisons between the three R_{Fv} levels, with an increase of SJ_{rep} when R_{Fv} decreases. A simple main effect of $\%P_{\text{max}}$ was observed at the highest level of R_{Fv} (p < 0.001), but not at the two lower levels (p = 0.129 and p = 0.782,

TABLE 1 | Mean ± SD of the maximum repetitions in P₃v₄ condition obtained from the two trials to assess intra-day and inter-day reliability analysis.

	Maximum	repetitions			Reliability	
	Trial 1	Trial 2	p-Value	SEM	Standardized SEM (inference)	ICC [95%CI]
Intra-day reliability	17.8 ± 7.6	16.9 ± 9.4	0.363	2.36	0.28 (small)	0.94 [0.83;0.98]
Inter-day reliability	17.8 ± 8.8	16.9 ± 9.4	0.480	2.79	0.31 (small)	0.92 [0.8;0.97]

TABLE 2 | Mean ± SD of additional load, intra-set RSJ jump height coefficient of variation and jumping frequency for the 10 F-v-P conditions.

		Additional load (kg)	Targeted jump height (cm)	Coefficient of variation (%)	Jumping frequency (Hz)
P 5	v ₆	11.2 ± 1.7	25.8 ± 5.4	1.98 ± 1.28	0.36 ± 0.04
P 4	V ₆	5.9 ± 1.2	25.8 ± 5.4	2.34 ± 0.75	0.35 ± 0.02
P ₃	V ₆	0.2 ± 0.5	25.8 ± 5.4	3.24 ± 0.78	0.35 ± 0.01
	V 4	19.9 ± 4.3	19.5 ± 4.4	3.35 ± 1.33	0.34 ± 0.01
	V ₃	46.9 ± 12.6	14.2 ± 3.7	3.39 ± 1.65	0.31 ± 0.05
2 2	v 5	0.1 ± 0.5	21.9 ± 4.8	4.58 ± 3.15	0.34 ± 0.01
	V ₃	31.3 ± 9.7	14.2 ± 3.7	5.22 ± 1.86	0.33 ± 0.02
	<i>v</i> ₂	68.8 ± 17.1	9.2 ± 2.6	6.04 ± 4.38	0.28 ± 0.05
P ₁	V ₃	15.6 ± 6.7	14.2 ± 3.7	5.89 ± 0.88	0.33 ± 0.02
	V 1	52.7 ± 14.3	8.7 ± 2.6	8.43 ± 3.98	0.32 ± 0.01

P_i: power output expressed relative to the power-velocity relationship; v_i: velocity expressed relative to the power-velocity relationship.

for the lowest and the middle level, respectively). A simple main effect of $R_{\rm Fv}$ was observed at the two levels of power (p < 0.001).

The two-way ANOVA with repeated measures testing the effect of $\%P_{\text{max}}$ and R_{Fv} on W_{tot} showed a main effect of R_{Fv} (p < 0.001) and $\%P_{\text{max}}$ (p < 0.001), and $R_{\text{Fv}} \times \%P_{\text{max}}$ interaction (p < 0.001; **Figure 4C**). *Post hoc* comparisons revealed significant differences for all comparisons between the three R_{Fv} levels (p < 0.001), with an increase of W_{tot} when R_{Fv} decreases. A simple main effect of $\%P_{\text{max}}$ was observed at the low level of R_{Fv} (p < 0.001), but not at the moderate and high levels (p = 0.954 et p = 0.323, respectively). There was a simple main effect of R_{Fv} at the two levels of power (p < 0.001).

Effect of R_{Fv} and $%P_{max}v$ on SJ_{rep} and W_{tot}

The two-way ANOVA with repeated measures testing the effect of $\[max] P_{\max} v$ and R_{Fv} on SJ_{rep} showed a main effect of R_{Fv} (p < 0.001) and $\[max] P_{\max} v$ (p < 0.001), and $R_{\text{Fv}} \times P_{\max} v$ interaction (p = 0.03; **Figure 4B**). *Post hoc* comparisons revealed significant differences in all comparisons between the three R_{Fv} levels (p < 0.05), with an increase of SJ_{rep} when R_{Fv} decreases. A simple main effect of $\[max] P_{\max} v$ was observed at each level of R_{Fv} (p < 0.001). There was a simple main effect of R_{Fv} at $85\% P_{\max} v$ (p < 0.001) and a trend at $100\% P_{\max} v$ (p = 0.078).

The two-way ANOVA with repeated measures testing the effect of $\%P_{\max}v$ and R_{Fv} on W_{tot} showed a main effect of R_{Fv} (p < 0.001) and $\%P_{\max}v$ (p < 0.001) and $R_{Fv} \times \%P_{\max}v$ interaction (p < 0.001; **Figure 4D**). Post hoc comparisons revealed significant differences at the three R_{Fv} levels (p < 0.05), with an increase of W_{tot} when R_{Fv} decreases. A simple main effect of $\%P_{\max}v$ was observed at the three levels of R_{Fv} (p < 0.001). There was a simple main effect of R_{Fv} observed at 85% $P_{\max}v$ (p < 0.001), but only a trend at 100% $P_{\max}v$ (p = 0.134).

DISCUSSION

The main finding of this study was that strength-endurance in repeated jumping depends on force, velocity, and power conditions, expressed relative to force- and power-velocity relationships. The large intra-individual differences in both the maximum repetitions and total work produced across the 10 *F*v-*P* conditions studied (from \sim 3 to \sim 150 repetitions and from \sim 2000 to \sim 70000 Joules) were almost entirely explained (\sim 98%) by both the velocity-specific relative power and the ratio between force and velocity to generate power. Strength-endurance was higher at lower velocity-specific relative power and in lower force-higher velocity conditions. Intra- and inter-day reliability of the RSJ test to exhaustion was acceptable and congruent with previously reported reliabilities for tests to exhaustion of approximately similar duration (e.g., Coggan and Costill, 1984; Hinckson and Hopkins, 2005).

In comparison to $%P_{\text{max}}$ and R_{Fv} , $%P_{\text{max}}v$ was the mechanical condition that affected the most strength-endurance (i.e., \sim 88–89% of the variance explained in SJ_{rep} and W_{tot}).% P_{max} was not a predictor of strength-endurance, notably since it does not consider the change in power capability with the force-velocity condition. Indeed, at the same $%P_{\text{max}}$, the power

	Maximum repetitions	Cumulated mechanical work (J)	Pow	Power (W)	Power	Power (%P _{max})	Power (%P _{max} v)	6P _{max} v)	Forc	Force (N)	Velocity (m.s ⁻¹)	(m.s ⁻¹)	Force-velocity ratio (R _{Fv})	ty ratio	Mechanical work (J)	l work (J)
			Targeted	Achieved	Targeted	Targeted Achieved Targeted	Targeted	Achieved	Targeted	Achieved	Targeted	Achieved	Targeted	Achieved	Targeted	Achieved
$P_5 v_6$	6.21 ± 4.56	4079 ± 2925	1466 ± 318	1466 ± 318 1422 ± 316	95.6 ± 2.4	92.5 ± 4.4	100.0 ± 0.0		1297 ± 169	$96.8 \pm 3.3 1297 \pm 169 1282 \pm 164 1.12 \pm 0.12 1.10 \pm 0.13 1.49 \pm 0.21 1.50 \pm 0.22 1.20 \pm 0.22 1.10 \pm 0.13 1.49 \pm 0.21 1.50 \pm 0.22 1.10 \pm 0.13 1.49 \pm 0.21 1.50 \pm 0.22 1.10 \pm 0.13 1.49 \pm 0.21 1.50 \pm 0.22 1.10 \pm 0.13 1.49 \pm 0.21 1.50 \pm 0.22 1.10 \pm 0.22 1.10 \pm 0.21 1.10 1.1$	1.12 ± 0.12	1.10 ± 0.13	1.49 ± 0.21	1.50 ± 0.22	587 ± 97	582 ± 103
P4 V6	17.00 ± 9.43	9288 ± 5381	1372 ± 298	1372 ± 298 1363 ± 294	89.4 ± 1.9	88.8 ± 2.6	93.6 ± 0.4		1213 ± 158	$92.9 \pm 1.0 1213 \pm 158 1213 \pm 157 1.12 \pm 0.12 1.11 \pm 0.12 1.40 \pm 0.21 1.40 \pm 0.21$	1.12 ± 0.12	1.11 ± 0.12	1.40 ± 0.21	1.40 土 0.21	555 ± 76	550 ± 99
P ₃ v ₆	58.79 ± 37.39	29702 ± 19616		1278 ± 279 1248 ± 262		85.0 ± 0.0 83.3 ± 2.0	85.0 ± 0.0	83.2 ± 2.0	1130 ± 148	$85.0\pm0.0\ \ 83.2\pm2.0\ \ 1130\pm148\ \ 1119\pm139\ \ 1.12\pm0.12\ \ 1.10\pm0.12\ \ 1.30\pm0.21\ \ 1.30\pm0.19$	1.12 ± 0.12	1.10 ± 0.12	1.30 ± 0.21	1.30 ± 0.19	512 ± 97	508 ± 89
V4	19.86 ± 7.47	12016 ± 5391	1278 ± 279	$1278 \pm 279 1270 \pm 275$		85.0 ± 0.0 84.9 ± 2.4		91.4 ± 2.0	1295 ± 167	$92.0 \pm 1.0 91.4 \pm 2.0 1295 \pm 167 1296 \pm 162 0.97 \pm 0.11 0.97 \pm 0.12 1.71 \pm 0.18 1.77 \pm 0.18 1.77$	0.97 ± 0.11	0.97 ± 0.12	1.71 ± 0.18	1.77 ± 0.18	590 ± 56	589 ± 102
V3	4.21 ± 2.97	2892 ± 2099	1278 ± 279	$1278 \pm 279 1240 \pm 247$	85.0 ± 0.0	86.5 ± 3.7	100.0 ± 0.0	97.3 ± 4.2	1518 ± 201	$85.0\pm0.0 86.5\pm3.7 100.0\pm0.0 97.3\pm4.2 1518\pm201 1506\pm188 0.83\pm0.11 0.82\pm0.10 2.37\pm0.10 2.41\pm0.12 2.41\pm0.12$	0.83 ± 0.11	0.82 ± 0.10	2.37 ± 0.10	2.41 ± 0.12	693 ± 117	686 ± 117
$P_2 v_5$	148.21 ± 88.56	70858 土 41274	1115 ± 245	1115 ± 254	72.6 ± 0.8	72.4 ± 1.8	78.3 ± 1.8	78.2 ± 2.3	1069 ± 137	$78.2 \pm 2.3 1069 \pm 137 1073 \pm 139 1.03 \pm 0.12 1.03 \pm 0.12 1.34 \pm 0.20 1.34 \pm 0.20$	1.03 ± 0.12	1.03 ± 0.12	1.34 ± 0.20	1.34 ± 0.20	490 ± 95	486 ± 87
V ₃	20.64 ± 10.97	11804 ± 6254	1115 ± 245	1112 ± 242	72.6 ± 0.8	72.4 ± 2.4	85.0 ± 0.0		1324 ± 173	84.9 ± 2.4 1324 ± 173 1324 ± 168	0.83 ± 0.11	0.83 ± 0.11 0.83 ± 0.11	2.07 ± 0.10	2.06 ± 0.12	611 ± 57	605 ± 105
V2	2.93 ± 2.53	2046 ± 1777	1115 ± 245	1057 ± 252	72.6 ± 0.8	68.9 ± 7.1	100.0 ± 0.0		1642 ± 222	$94.9\pm9.4 1642\pm222 1616\pm219 0.67\pm0.10 0.65\pm0.10$	0.67 ± 0.10	0.65 ± 0.10	3.19 ± 0.07	3.26 ± 0.20	746 ± 60	739 ± 123
P ₁ v ₃	P₁ v3 124.07 ± 86.76	62586 ± 44091	951 ± 211	964 ± 218	61.9 ± 0.7	62.5 ± 1.6	74.3 ± 1.6	75.1 ± 2.4	1129 ± 145	74.3 ± 1.6 75.1 ± 2.4 1129 ± 145 1136 ± 144 0.83 ± 0.11 0.84 ± 0.11 1.76 ± 0.11	0.83 ± 0.11	0.84 ± 0.11	1.76 ± 0.11	1.76 ± 0.11	523 ± 101	518 ± 90
7	12.64 ± 6.85	8455 ± 5203	951 ± 211	969 ± 222		61.9 ± 0.7 62.9 ± 2.9	85.0 ± 0.0	86.5 ± 3.6	1444 ± 193	$85.0 \pm 0.0 86.5 \pm 3.6 1444 \pm 193 1453 \pm 190 0.65 \pm 0.10 0.66 \pm 0.10 2.89 \pm 0.07 2.85 \pm 0.13 0.13 \pm 0.01 0.14 \pm 0.01 0.01$	0.65 ± 0.10	0.66 ± 0.10	2.89 ± 0.07	2.85 ± 0.13	674 ± 104	668 ± 118



FIGURE 4 The maximum repetitions (**A**,**B**) and cumulated mechanical work (**C**,**D**), presented on a natural logarithmic scale at different velocities, at \sim 73%P_{max} (black) and 85%P_{max} (gray) on the (**A**,**C**), and at 85%P_{max} v (black) and 100%P_{max} v (gray) on the (**B**,**D**). The force-velocity ratio values associated to each condition are presented in black text. Power and force-velocity ratio main effects of the two-way ANOVAs for repeated measures are presented as black vertical and horizontal bars, respectively, with the associated *p*-values.

output relative to the velocity-specific P_{max} (i.e., $P_{\text{max}}v$) can be drastically different according to the force-velocity conditions and lead to substantial differences in strength endurance performance. It is worth noting that among the 10 F-v-P conditions, a lower %P_{max} was not systematically associated with a higher strength-endurance. For example, the 3 F-v-P conditions at \sim 85%P_{max}, \sim 73%P_{max}, and \sim 62%P_{max} were associated with performances of ~58, ~21, and 12 repetitions, respectively. This further highlights the inability of $\%P_{\text{max}}$ to represent exercise intensity, notably when the exercises are not performed in the same force-velocity condition. Since the force-velocity condition varies during field performance and physical testing due to changing loading/resistive conditions and levers/equipment used, the common implementation of $%P_{\text{max}}$ to represent exercise intensity could be challenged (e.g., Harman et al., 1987; Bundle et al., 2003). Instead, it appears that $%P_{\max}v$ better represents exercise intensity, since it considers the change in the individual maximal power capabilities according to the force-velocity condition. Thus, strength endurance seems to depend primarily on power output, expressed relative to the velocity-specific maximal power, and not to the maximal power value developed at optimal velocity. This supports the importance of the power reserve (Sargeant, 1994, 2007; Zoladz

et al., 2000), and in turn, the influence of maximal power capabilities (i.e., the P- ν relationship) on the individual ability to maintain sub-maximal power over time, notably at high exercise intensities.

The second strongest mechanical predictor of strengthendurance was $R_{\rm Fv}$, which explained ~8–9% of the variance in SJ_{Rep} and W_{tot} . Note that the remaining variance (~2-3%) is likely due to measurement errors. Decreasing $R_{\rm Fv}$ (i.e., increasing movement velocity and decreasing the force output at matched $\%P_{\text{max}}$ or $\%P_{\text{max}}\nu$) resulted in increased strengthendurance. These results confirm that, when standardizing rest time between repetitions, a change in force-velocity condition influences strength-endurance independently from a change in $%P_{\max}v$ (Figures 4B,D) or a change in $%P_{\max}$ (Figures 4A,C). These findings contrast previous hypotheses suggesting that increasing movement velocity is unbeneficial (Mathiassen, 1989; Carnevale and Gaesser, 1991; Morel et al., 2015), notably due to potentially higher proportions of fatigable type II muscle fiber recruitment (Beelen and Sargeant, 1991b; Blake and Wakeling, 2014). However, as these studies did not use standardized rest time between contractions and fixed repetitions across velocity conditions, the negative effect of low rest time in high-frequency conditions could have counteracted



the positive effect of movement velocity. Additionally, as mechanical work per repetition was different across all Fv-P conditions, the total mechanical work produced until exhaustion is likely a better index of strength endurance, even if less practically relevant. However, although $R_{\rm Fy}$ explained a comparatively small part of the overall variance, its change led to substantial differences in strength-endurance (e.g., ~ 13 , ~ 20 , and ~ 60 repetitions at $85\% P_{\text{max}}\nu$, with associated $R_{\rm Fv}$ mean values of ~2.9, ~2.1, ~1.3, respectively). It is worth noting that, the influence of $R_{\rm Fv}$ on strengthendurance can change according to $\%P_{\max}v$, as shown by the significant $R_{\rm Fv} \times P_{\rm max} v$ interaction. Indeed, the effect of $R_{\rm Fv}$ is further magnified at lower % $P_{\rm max}v$ (Figures 4B,D). Taken together, these results show that increases in velocity and decreases in force at the same $%P_{\max}v$ or $%P_{\max}$ during acyclic movements (e.g., repeated jumps or callisthenic exercises) are rather beneficial than detrimental and could lead to substantial change in maximum repetitions and cumulated work until exhaustion. Strength-endurance at the individual level seems to be almost fully dependent on F-v-P conditions, expressed relative to the individualized F-v and Pv relationships. More specifically, performance is determined by the position of the exercise mechanical conditions on or under the F-v and P-v relationships, this position being characterized by $\[mathcar{e}] P_{\max} \nu$ and R_{Fv} (expressed relative to F_0 and v_0 ; Figure 5).

Limitations of the Study

One limitation of this study is the restricted range investigated relative to the entire P-v spectrum, and coincidentally the extrapolation of the results on the effect of $\% P_{\max} v$ and R_{Ev} on strength-endurance beyond the optimal velocity. However, the range of movement velocities explored was maximized considering conditions occurring in sports activities (i.e., inertial and resistive conditions close to bodyweight and higher). The range of power explored was also nearly maximized, from maximal jump height to jump height of ~ 10 cm with different loadings. The latter was proposed as a cut-off jump height for accurate assessment of force, velocity and power output with the practical field method used in this study (García-Ramos et al., 2018). Also, although rest time between contractions was controlled in the present study, slight differences were observed in jumping frequencies across F-v-P conditions. However, due to the specificity of the RSJ test, other main mechanisms associated to the negative effect of movement frequency, that is, the lower effectiveness of force application (Dorel et al., 2010) and higher internal work (Zoladz et al., 2000) may have minorly affected our results. Another limitation is the focus on the understanding of the difference in strength-endurance between different F-v-P mechanical conditions, without considering inter-individual differences. Qualifying the physical abilities underlying differences in strength-endurance for two participants in the same $%P_{max}v$ and R_{Fv} would be a beneficial avenue of investigation for future research.

Practical Applications and Perspectives for Future Studies

- Strength-endurance evaluation should be standardized according to the individual F-v and P-v relationships, notably via % $P_{\max}v$ and R_{Fv} , rather than to (i) a given percentage of maximal force (Mayhew et al., 1992), (ii) the same movement velocity across individuals (Câmara et al., 2012), or (iii) the same resistive force per bodyweight during all-out cycling exercises (Bar-Or, 1987). Without such standardization, inter-individual differences in strength-endurance could be mainly due to different % $P_{\max}v$ and R_{Fv} conditions among individuals and not only a marker of different physical abilities. Such "Force-velocity-Power based training" could ensure strength and conditioning to improve the strength-endurance of athletes in competition-specific % $P_{\max}v$ and R_{Fv} conditions.
- Similarly, standardizing dynamic fatiguing protocols and the subsequent fatigue assessment only relative to $%P_{max}$ or maximal isometric force (Millet et al., 2011) could be challenged since each individual may experience different $%P_{max}v$ and R_{Fv} conditions during both phases of such experimentation. Thus, it is likely that the typical high inter-individual variability response in fatigue level (Morel et al., 2019) could be explained by the non-consideration of *F-v-P* conditions under which the evaluation or the effort was performed.

• RSJ is a reliable, practical, and modifiable method to evaluate lower limb strength-endurance in a broad range of exercise conditions specific to field situations. Indeed, the results of the present study showed that strength-endurance assessment in jumping exhibited acceptable absolute and almost perfect relative intra- and inter-day reliability. These values are in agreement with those reported in cycling for efforts of approximately similar duration (e.g., Coggan and Costill, 1984; Hinckson and Hopkins, 2005). The only requirements of an RSJ test are the measurements of body mass, pushoff distance and continuous jump height over successive repetitions, and the use of Samozino et al's validated simple method to estimate force, velocity, and power in jumping (Samozino et al., 2008; Giroux et al., 2014; Jiménez-Reves et al., 2014; García-Ramos et al., 2019). Notably, there are many convenient methods of detecting the necessary variables (e.g., phone applications or other common devices, such as optical systems). Since different sporting scenarios involving repeated lower limb extensions feature different underlying expressions of movement frequency, force, velocity, and power output (e.g., volley-ball vs. skiing disciplines), it is possible to adapt these mechanical conditions through manipulating rest time, loading, and jump height. While the RSJ test is relatively simplistic, non-familiar cohorts of participants should be well-familiarized to ensure reasonable accuracy and reliability of assessment (Hopkins et al., 2001).

CONCLUSION

Strength-endurance in jumping, either characterized as the maximum repetitions or cumulated mechanical work performed until exhaustion, depends on both the velocity-specific relative power (or the power reserve) and the underlying force-velocity condition. Strength-endurance was higher when velocity-specific relative power was lower (i.e., larger power reserve) and when the force-velocity condition to generate power was oriented toward low force-high velocity (at least until optimal velocity). The RSJ is a reliable and practical method to assess strength-endurance of the lower limbs, with the possibility to easily set these mechanical

REFERENCES

- Alcazar, J., Rodriguez-Lopez, C., Ara, I., Alfaro-Acha, A., Mañas-Bote, A., Guadalupe-Grau, A., et al. (2017). The force-velocity relationship in older people: reliability and validity of a systematic procedure. *Int. J. Sports Med.* 38, 1097–1104. doi: 10.1055/s-0043-119880
- Asmussen, E., and Bonde-Petersen, F. (1974). Storage of elastic energy in skeletal muscles in man. *Acta Physiol. Scand.* 91, 385–392. doi: 10.1111/j.1748-1716. 1974.tb05693.x
- Barker, T., Poole, D. C., Noble, M. L., and Barstow, T. J. (2006). Human critical power-oxygen uptake relationship at different pedalling frequencies. *Exp. Physiol.* 91, 621–632. doi: 10.1113/expphysiol.2005.032789
- Bar-Or, O. (1987). The wingate anaerobic test. Sport Med. 4, 381–394. doi: 10.2165/ 00007256-198704060-00001
- Beelen, A., and Sargeant, A. J. (1991a). Effect of fatigue on maximal power output at different contraction velocities in humans. J. Appl. Physiol. 71, 2332–2337. doi: 10.1152/jappl.1991.71.6.2332

conditions, by manipulating jump height, loading and rest time between jumps. Strength-endurance in acyclic movements depends on the position of the exercise mechanical conditions, in terms of relative force, velocity and power, which can be situated on or under the force-velocity and power-velocity relationships. Since maximal capabilities (i.e., force- and power-velocity relationships) and the exercise mechanical conditions (i.e., forcevelocity condition and velocity-specific relative power) influence strength-endurance performances, both should be controlled and targeted to standardize testing and training between individuals and to explore underlying mechanisms of fatigue.

DATA AVAILABILITY STATEMENT

The raw data supporting the conclusions of this article will be made available by the authors, without undue reservation.

ETHICS STATEMENT

The studies involving human participants were reviewed and approved by Comité d'Ethique de la Recherche à l'Université Savoie Mont Blanc. The patients/participants provided their written informed consent to participate in this study.

AUTHOR CONTRIBUTIONS

JR, PS, NP, and LM conceived and designed the experimentation. JR conducted the experiments and wrote the manuscript. JR, MC, and PS analyzed the data. All authors read and approved the manuscript.

ACKNOWLEDGMENTS

We would like to show our gratitude to Pr. J.-B. Morin, Dr. S. Dorel, Dr. C. Nicol and Pr. G. Dalleau for their valuable discussions about the results of this study.

- Beelen, A., and Sargeant, A. J. (1991b). Effect of prior exercise at different pedalling frequencies on maximal power in humans. *Eur. J. Appl. Physiol. Occup. Physiol.* 66, 102–107. doi: 10.1007/BF01427049
- Bessot, N., Nicolas, A., Moussay, S., Gauthier, A., Sesboüé, B., and Davenne, D. (2006). The effect of pedal rate and time of day on the time to exhaustion from high-intensity exercise. *Chronobiol. Int.* 23, 1009–1024. doi: 10.1080/ 07420520600920726
- Blake, O. M., and Wakeling, J. M. (2014). Early deactivation of slower muscle fibres at high movement frequencies. J. Exp. Biol. 217, 3528–3534. doi: 10.1242/jeb. 108266
- Bobbert, M. F. (2012). Why is the force-velocity relationship in leg press tasks quasi-linear rather than hyperbolic? J. Appl. Physiol. 112, 1975–1983. doi: 10. 1152/japplphysiol.00787.2011
- Broxterman, R. M., Ade, C. J., Wilcox, S. L., Schlup, S. J., Craig, J. C., and Barstow, T. J. (2014). Influence of duty cycle on the power-duration relationship: observations and potential mechanisms. *Respir. Physiol. Neurobiol.* 192, 102– 111. doi: 10.1016/j.resp.2013.11.010

- Bundle, M. W., Hoyt, R. W., and Weyand, P. G. (2003). Highspeed running performance: a new approach to assessment and prediction. J. Appl. Physiol. 95, 1955–1962. doi: 10.1152/japplphysiol.009 21.2002
- Burnley, M., and Jones, A. M. (2016). Power-duration relationship: physiology, fatigue, and the limits of human performance. *Eur. J. Sport Sci.* 18, 1–12. doi: 10.1080/17461391.2016.1249524
- Câmara, L. C., Ritti-Dias, R. M., Menêses, A. L., D'Andréa Greve, J. M., Filho, W. J., Santarém, J. M., et al. (2012). Isokinetic strength and endurance in proximal and distal muscles in patients with peripheral artery disease. *Ann. Vasc. Surg.* 26, 1114–1119. doi: 10.1016/j.avsg.2012. 03.012
- Carnevale, T. J., and Gaesser, G. A. (1991). Effects of pedaling speed on the powerduration relationship for high-intensity exercise. *Med. Sci. Sports Exerc.* 23, 242–246.
- Coggan, A. R., and Costill, D. L. (1984). Biological and technological variability of three anaerobic ergometer tests. *Int. J. Sports Med.* 5, 142–145. doi: 10.1055/s-2008-1025896
- Dalton, B. H., Power, G. A., Vandervoort, A. A., and Rice, C. L. (2012). The agerelated slowing of voluntary shortening velocity exacerbates power loss during repeated fast knee extensions. *Exp. Gerontol.* 47, 85–92. doi: 10.1016/j.exger. 2011.10.010
- Dorel, S., Bourdin, M., Van Praagh, E., Lacour, J.-R., and Hautier, C. A. (2003). Influence of two pedalling rate conditions on mechanical output and physiological responses during all-out intermittent exercise. *Eur. J. Appl. Physiol.* 89, 157–165. doi: 10.1007/s00421-002-07 64-4
- Dorel, S., Couturier, A., Lacour, J. R., Vandewalle, H., Hautier, C., and Hug, F. (2010). Force-velocity relationship in cycling revisited: benefit of twodimensional pedal forces analysis. *Med. Sci. Sports Exerc.* 42, 1174–1183. doi: 10.1249/MSS.0b013e3181c91f35
- Elert, J., and Gerdle, B. (1989). The relationship between contraction and relaxation during fatiguing isokinetic shoulder flexions. An electromyographic study. *Eur. J. Appl. Physiol. Occup. Physiol.* 59, 303–309. doi: 10.1007/BF023 88333
- Enoka, R. M., and Stuart, D. G. (1992). Neurobiology of muscle fatigue. J. Appl. Physiol. 72, 1631–1648. doi: 10.1152/jappl.1992.72.5.1631
- García-Ramos, A., Pérez-Castilla, A., and Jaric, S. (2018). Optimisation of applied loads when using the two-point method for assessing the force-velocity relationship during vertical jumps. *Sport Biomech.* [Epub ahead of print]. doi: 10.1080/14763141.2018.1545044
- García-Ramos, A., Pérez-Castilla, A., Morales-Artacho, A. J., Almeida, F., Padial, P., Bonitch-Góngora, J., et al. (2019). Force-velocity relationship in the countermovement jump exercise assessed by different measurement methods. *J. Hum. Kinet.* 67, 37–47. doi: 10.2478/hukin-20 18-0085
- Giroux, C., Rabita, G., Chollet, D., and Guilhem, G. (2014). What is the best method for assessing lower limb force-velocity relationship? *Int. J. Sports Med.* 36, 143–149. doi: 10.1055/s-0034-1385886
- Harman, E. A., Knuttgen, H. G., Frykman, P. N., and Patton, J. F. (1987). Exercise endurance time as a function of percent maximal power production. *Med. Sci. Sports Exerc.* 19, 480–485.
- Hinckson, E. A., and Hopkins, W. G. (2005). Reliability of time to exhaustion analyzed with critical-power and log-log modeling. *Med. Sci. Sports Exerc.* 37, 696–701. doi: 10.1249/01.MSS.0000159023. 06934.53
- Hopkins, W. G., Schabort, E. J., and Hawley, J. A. (2001). Reliability of power in physical performance tests. Sport Med. 31, 211–234. doi: 10.2165/00007256-200131030-00005
- Janicijevic, D., Knezevic, O. M., Mirkov, D. M., Pérez-Castilla, A., Petrovic, M., Samozino, P., et al. (2019). Assessment of the force-velocity relationship during vertical jumps: influence of the starting position, analysis procedures and number of loads. *Eur. J. Sport Sci.* 20, 614–623. doi: 10.1080/17461391.2019. 1645886
- Janicijevic, D. N., Knezevic, O. M., Mirkov, D. M., Pérez-Castilla, A., Petrovic, M. R., and García-Ramos, A. (2019). Magnitude and reliability of mechanical outputs obtained during loaded squat jumps performed from different knee

angles. Sport Biomech. [Epub ahead of print]. doi: 10.1080/14763141.2019. 1618390

- Jaric, S. (2015). Force-velocity relationship of muscles performing multi-joint maximum performance tasks. Int. J. Sports Med. 36, 699–704. doi: 10.1055/s-0035-1547283
- Jiménez-Reyes, P., Samozino, P., Cuadrado-Peñafiel, V., Conceição, F., González-Badillo, J., and Morin, J.-B. (2014). A simple method to measure force-velocity profile in counter movement jump. *Br. J. Sports Med.* 48, A3.2–A3.3. doi: 10.1136/bjsports-2014-094245.9
- Jones, A. M., and Vanhatalo, A. (2017). The ' critical power ' concept? applications to sports performance with a focus on intermittent high-intensity exercise. *Sport Med.* 47, 65–78. doi: 10.1007/s40279-01 7-0688-0
- Karsten, B., Hopker, J., Jobson, S. A., Baker, J., Petrigna, L., Klose, A., et al. (2016). Comparison of inter-trial recovery times for the determination of critical power and W' in cycling. *J. Sports Sci.* 35, 1420–1425. doi: 10.1080/02640414.2016. 1215500
- Landis, J. R., and Koch, G. G. (1977). The measurement of observer agreement for categorical data. *Biometrics* 33, 159–174. doi: 10.2307/252 9310
- Leveque, J. M., Brisswalter, J., Bernard, O., and Goubault, C. (2002). Effect of paddling cadence on time to exhaustion and kinetics at the intensity associated with in elite white-water kayakers. *Can. J. Appl. Physiol.* 27, 602–611. doi: 10.1139/h02-035
- Mathiassen, S. E. (1989). Influence of angular velocity and movement frequency on development of fatigue in repeated isokinetic knee extensions. *Eur. J. Appl. Physiol. Occup. Physiol.* 59, 80–88. doi: 10.1007/BF0239 6584
- Mayhew, J. L., Ball, T. E., Arnold, M. D., and Bowen, J. C. (1992). Relative muscular endurance performance as a predictor of bench press strength in college men and women. *J. Strength Cond. Res.* 6, 200–206. doi: 10.1519/00124278-199211000-00002
- Millet, G. Y., Martin, V., Martin, A., and Vergès, S. (2011). Electrical stimulation for testing neuromuscular function: from sport to pathology. *Eur. J. Appl. Physiol.* 111, 2489–2500. doi: 10.1007/s00421-011-1996-y
- Monod, H., and Scherrer, J. (1965). The work capacity of a synergic muscular group. Ergonomics 8, 329–338. doi: 10.1080/00140136508930810
- Morel, B., Clémençon, M., Rota, S., Millet, G. Y., Bishop, D. J., Brosseau, O., et al. (2015). Contraction velocity influence the magnitude and etiology of neuromuscular fatigue during repeated maximal contractions. *Scand. J. Med. Sci. Sport* 25, e432–e441. doi: 10.1111/sms.12358
- Morel, B., Lapole, T., Liotard, C., and Hautier, C. (2019). Critical peripheral fatigue thresholds among different force-velocity conditions: an individualbased model approach. *Front. Physiol.* 10:875. doi: 10.3389/fphys.2019. 00875
- Sainani, K. L. (2012). Dealing with non-normal data. PM R 4, 1001–1005. doi: 10.1016/j.pmrj.2012.10.013
- Samozino, P., Edouard, P., Sangnier, S., Brughelli, M., Gimenez, P., and Morin, J. B. (2014). Force-velocity profile: imbalance determination and effect on lower limb ballistic performance. *Int. J. Sports Med.* 35, 505–510. doi: 10.1055/s-0033-1354382
- Samozino, P., Morin, J.-B., Hintzy, F., and Belli, A. (2008). A simple method for measuring force, velocity and power output during squat jump. J. Biomech. 41, 2940–2945. doi: 10.1016/j.jbiomech.2008.07.028
- Samozino, P., Rejc, E., Di Prampero, P. E., Belli, A., and Morin, J.-B. (2012). Optimal force-velocity profile in ballistic movements—altius. *Med. Sci. Sport Exerc.* 44, 313–322. doi: 10.1249/MSS.0b013e318 22d757a
- Sargeant, A. J. (1994). Human power output and muscle fatigue. *Int. J. Sports Med.* 15, 116–121. doi: 10.1055/s-2007-1021031
- Sargeant, A. J. (2007). Structural and functional determinants of human muscle power. *Exp. Physiol.* 92, 323–331. doi: 10.1113/expphysiol.2006. 034322
- Sargeant, A. J., Hoinville, E., and Young, A. (1981). Maximum leg force and power output during short-term dynamic exercise. J. Appl. Physiol. 51, 1175–1182. doi: 10.1152/jappl.1981.51.5.1175

- Tomas, A., Ross, E. Z., and Martin, J. C. (2010). Fatigue during maximal sprint cycling: unique role of cumulative contraction cycles. *Med. Sci. Sport. Exerc.* 42, 1364–1369. doi: 10.1249/MSS.0b013e31 81cae2ce
- Triska, C., Karsten, B., Nimmerichter, A., and Tschan, H. (2017). Iso-duration determination of d' and cs under laboratory and field conditions. *Int. J. Sports Med.* 38, 527–533. doi: 10.1055/s-0043-102943
- Zoladz, J. A., Rademaker, A. C. H. J., and Sargeant, A. J. (2000). Human muscle power generating capability during cycling at different pedalling rates. *Exp. Physiol.* 85, 117–124. doi: 10.1111/j.1469-445X.2000.01 840.x

Conflict of Interest: The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

Copyright © 2020 Rivière, Peyrot, Cross, Messonnier and Samozino. This is an open-access article distributed under the terms of the Creative Commons Attribution License (CC BY). The use, distribution or reproduction in other forums is permitted, provided the original author(s) and the copyright owner(s) are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.