## Check for updates

## **OPEN ACCESS**

APPROVED BY Frontiers Editorial Office, Frontiers Media SA, Switzerland

\*CORRESPONDENCE Frontiers Production Office, production.office@frontiersin.org

RECEIVED 02 June 2023 ACCEPTED 02 June 2023 PUBLISHED 19 June 2023

#### CITATION

Frontiers Production Office (2023), Erratum: A low-power magnetorheological fluid clutch utilizing electropermanent magnet arrays. *Front. Mater.* 10:1233628. doi: 10.3389/fmats.2023.1233628

#### COPYRIGHT

© 2023 Frontiers Production Office. This is an open-access article distributed under the terms of the Creative Commons Attribution License (CC BY). The use, distribution or reproduction in other forums is permitted, provided the original author(s) and the copyright owner(s) are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.

# Erratum: A low-power magnetorheological fluid clutch utilizing electropermanent magnet arrays

# Frontiers Production Office\*

Frontiers Media SA, Lausanne, Switzerland

#### KEYWORDS

magnetorheological fluid, electropermanent magnet, magnet, electromagnet, clutch, low-power

### An Erratum on

A low-power magnetorheological fluid clutch utilizing electropermanent magnet arrays

by Bira N, Dhagat P and Davidson JR (2022). Front. Mater. 9:1039004. doi: 10.3389/fmats.2022. 1039004

Due to a production error, there was a mistake in the legend for Figure 11 as published. The legend for Figure 11 was accidentally removed during typesetting. The correct legend appears below. The publisher apologizes for this mistake.

The original version of this article has been updated.

# Publisher's note

All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors, and the reviewers. Any product that may be evaluated in this article, or claim that may be made by its manufacturer, is not guaranteed or endorsed by the publisher.



## FIGURE 11

The change in average transmitted torque as a function of pulse length for the MEC. Polarization requires greater pulse lengths to achieve the largest possible transmitted torque, while depolarization can have larger changes with shorter pulse lengths.