



OPEN ACCESS

EDITED AND REVIEWED BY
Geoffrey Robert Mitchell,
Polytechnic Institute of Leiria, Portugal

*CORRESPONDENCE
Necim Kaya,
✉ necim.kaya@batman.edu.tr

RECEIVED 23 July 2025
ACCEPTED 02 September 2025
PUBLISHED 24 September 2025

CITATION
Kaya N (2025) Correction: Effect of different
fly ash ratios on the mechanical properties of
hybrid steel fiber reinforced concrete.
Front. Mater. 12:1671716.
doi: 10.3389/fmats.2025.1671716

COPYRIGHT
© 2025 Kaya. This is an open-access article
distributed under the terms of the [Creative
Commons Attribution License \(CC BY\)](#). The
use, distribution or reproduction in other
forums is permitted, provided the original
author(s) and the copyright owner(s) are
credited and that the original publication in
this journal is cited, in accordance with
accepted academic practice. No use,
distribution or reproduction is permitted
which does not comply with these terms.

Correction: Effect of different fly ash ratios on the mechanical properties of hybrid steel fiber reinforced concrete

Necim Kaya*

Department of Technologies Construction, Vocational School of Technical Sciences, Batman University, Batman, Türkiye

KEYWORDS

fly ash, concrete, steel fiber, hybrid fiber, mechanical properties

A Correction on Effect of different fly ash ratios on the mechanical properties of hybrid steel fiber reinforced concrete

by Kaya N. (2025). *Front. Mater.* 12:1585291. doi: 10.3389/fmats.2025.1585291

In the published article, there was an error in [Table 3](#). Mixture Proportions for 1 m³ of Concrete Series (kg) as published. The corrected [Table 3](#) and its caption appear below.
The original article has been updated.

Publisher's note

All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors and the reviewers. Any product that may be evaluated in this article, or claim that may be made by its manufacturer, is not guaranteed or endorsed by the publisher.

TABLE 3 Mixture proportions for 1 m³ of concrete series (kg).

Materials	H	U5H	U15H	U25H
Cement	475	451.25	403.75	356.25
Fly ash		17.62	52.85	88.1
Water	190	190	190	190
0–4 mm Aggregate	661.1	661.1	661.1	661.1
4–8 mm Aggregate	413.2	413.2	413.2	413.2
4–16 mm Aggregate	578.5	578.5	578.5	578.5
Superplasticizer	2.38	2.38	2.38	2.38
Steel Fiber 1 (SF1)	39.25	39.25	39.25	39.25
Steel Fiber 2 (SF2)	35.9	35.9	35.9	35.9